



SAFETY DATA SHEET

Section 1: Product and Company Identification

<i>Product Identifier:</i>	Nozzle Gel	
<i>Product Use:</i>	Protection of welding tips and nozzles; prevention of spatter build-up in weld operations	
<i>Item Code:</i>	108-16	<i>Nozzle Dip prevents Spatter Build up power Weld Quality welding products</i>
<i>Supplier Name:</i>	PowerWeld Inc.	
<i>Supplier Address:</i>	2501 Beech Street Valparaiso, IN 46383	
<i>Supplier Web Address:</i>	www.powerweldinc.com	
<i>Supplier Phone:</i>	219-462-8700 1-800-826-9073	
<i>Emergency Phone:</i>	CHEMTREC (24-Hour) 1-800-424-9300	
<i>Prepared By:</i>	PowerWeld Inc.	
<i>Preparation Date:</i>	17 November 2015	

Section 2: Hazard Identification

<i>Classification:</i>	Not a controlled product
<i>Label Elements:</i>	Not applicable
<i>Other Hazards:</i>	Not applicable

Section 3: Composition/Information on Hazardous Ingredients

HAZARDOUS INGREDIENTS	CAS NUMBER	APPROXIMATE CONCENTRATION (%)
Petrolatum	8009-03-08	>99%
Anthraquinone Dye	14233-37-5	<1%

Section 4: First-aid Measures

<i>Inhalation:</i>	If breathed in, move person to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration and transport to nearest medical facility for additional treatment.
<i>Ingestion:</i>	Wash out mouth with water. Do NOT induce vomiting. Call physician immediately. Never give anything by mouth to an unconscious person.
<i>Eye Contact:</i>	Immediately flush upper and lower eyelids with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Rest eyes for 30 minutes. If redness, burning, blurred vision or swelling persists, visit nearest medical facility for additional treatment.
<i>Skin Contact:</i>	Wash off with soap and water. Wash contaminated clothing before reuse. If skin irritation persists, contact a physician.

NOTE: In all severe cases, contact physician immediately. Local telephone operators can provide number of regional poison control centre.

Section 5: Fire-fighting Measures

<i>Flammable:</i>	No specific fire or explosion hazard. Will support a flame above flashpoint.
<i>Means of Extinction:</i>	Use an extinguishing agent suitable for the surrounding fire.
<i>Flashpoint:</i>	Greater than 165°C (329°F)
<i>Auto-ignition Temperature:</i>	Not available
<i>Hazardous Combustion Products:</i>	CO ₂ , CO
<i>Explosion Data Sensitivity to Mechanical Impact:</i>	Not available
<i>Explosion Data Sensitivity to Static Discharge:</i>	Not available
<i>Special Equipment:</i>	Wear full fire-fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
<i>Precautions for Fire Fighters:</i>	Keep personnel removed and upwind of any fire. Use water to keep containers cool.

Section 6: Accidental Release Measures

<i>Protection Equipment:</i>	See section 8
<i>Emergency Procedures:</i>	Prevent entry of product into sewers, water course, basements or confined areas.
<i>Leak or Spill Procedure:</i>	For <i>small spill</i> , move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. For <i>large spill</i> , move containers from spill area while preventing entry of product into sewers, water course, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container for disposal in accordance with local, provincial/state and federal regulations.

Section 7: Handling and Storage

<i>Handling Procedures and Equipment:</i>	Ensure proper PPE is being worn when handling product (see section 8). Handle in accordance with good industrial hygiene and safety practices. Do not eat, drink or smoke when using this product. Wash hands thoroughly before breaks and at the end of the workday.
<i>Storage Requirements:</i>	Store in original container away from direct sunlight.
<i>Incompatibilities:</i>	Strong oxidizing agents (ie./ peroxides, chlorines, etc.)

Section 8: Exposure Controls/Personal Protection

<i>Exposure Limits:</i>	Not applicable
<i>Engineering Controls:</i>	No special ventilation requirements; good general ventilation should be sufficient to control exposure to airborne contaminants.
<i>Personal Protective Equipment:</i>	<u>Respiratory:</u> If a risk assessment indicates respiratory protection is necessary, be sure to use a properly fitted particulate filter respirator. <u>Hands:</u> If product is in molten state, be sure to wear chemical-resistant, impervious gloves complying with an approved standard. <u>Eyes:</u> If product is in molten state, safety glasses with side shields or face shield should be worn to prevent splashes or mists. <u>Skin:</u> If product is in molten state, coveralls in compliance with an approved standard are recommended.

Section 9: Physical and Chemical Properties

<i>Physical State:</i>	Waxy solid
<i>Odour and Appearance:</i>	Hydrocarbon and blue
<i>Odour Threshold (ppm):</i>	Not available
<i>pH:</i>	Not available
<i>Melting Point:</i>	55.2°C (131.4°F)
<i>Freezing Point:</i>	Not available
<i>Boiling Point:</i>	302°C (575.6°F)
<i>Flashpoint:</i>	Closed cup: 182°C to 221°C (359.6°F to 429.8°F) Open cup: >200°C (>392°F)
<i>Relative Density:</i>	0.844
<i>Upper Flammable Limit (% by volume):</i>	7%
<i>Lower Flammable Limit (% by volume):</i>	0.9%

Section 10: Stability and Reactivity

<i>Chemical Stability:</i>	Stable
<i>Possible Hazardous Reactions:</i>	Not applicable
<i>Conditions to Avoid:</i>	Not applicable
<i>Materials to Avoid (Incompatibilities):</i>	Not applicable
<i>Conditions of Reactivity:</i>	Not applicable
<i>Hazardous Decomposition By-Products:</i>	Not applicable
<i>Hazardous Polymerization:</i>	Not applicable

Section 11: Toxicological Information

<i>Effects of Acute Exposure:</i>	Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product could cause thermal burns on contact with the skin and eyes. Breathing fumes in confined areas could cause respiratory irritation.
<i>Effects of Chronic Exposure:</i>	In rats, chronic ingestion of paraffins has shown accumulation in target organs (liver, spleen) with associated nonspecific immune response. Aspiration of large amounts is reported to cause lipid pneumonia.
<i>Irritancy of Product:</i>	Not available
<i>Sensitization to Product:</i>	Not applicable
<i>Carcinogenicity:</i>	Not applicable
<i>Reproductive Effects:</i>	Not applicable
<i>Respiratory Sensitization:</i>	Not applicable
<i>Toxicological Data:</i>	Dermal, rabbit - >5000 mg/kg (LD50); Oral, rat - >5000 mg/kg (LD50)

Section 12: Ecological Information

<i>Aquatic and Terrestrial Toxicity:</i>	Not available
<i>Persistence and Degradability:</i>	Not available
<i>Bioaccumulative Potential:</i>	Not available
<i>Soil Mobility:</i>	Not available

Section 13: Disposal Considerations

NOTE: Always dispose of waste in accordance with local, provincial and federal regulations.

Safe Handling:
Methods of Disposal:

See section 8.
Waste of this product should be avoided when possible. All waste should be disposed of in accordance to local, provincial/state and federal regulations.

Section 14: Transportation Information

This product is not regulated as it is not a controlled product.

Section 15: Regulatory Information

This product is not regulated.

Section 16: Other Information

Preparation Date: 17 November 2015
Date of Last Revision: 17 November 2015

This SDS format is in accordance with GHS. PowerWeld Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond the control of PowerWeld. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, expressed or implied, are made.