

QUIKRETE**CEMENT & CONCRETE PRODUCTS™**QUIKRETE GRAY CONCRETE
CRACK SEAL NO. 8640**A11: Water Based Products****SAFETY DATA SHEET**
(Complies with OSHA 29 CFR 1910.1200)**SECTION I: PRODUCT IDENTIFICATION**The QUIKRETE® Companies
One Securities Centre
3490 Piedmont Road, Suite 1300
Atlanta, GA 30305Emergency Telephone Number
(770) 216-9580
Information Telephone Number
(770) 216-9580SDS A11
Revision: Feb-16**QUIKRETE® Product Name**CONCRETE CRACK SEAL ←
BLACKTOP CRACK SEAL**Code #**→ 8640-00
8640-05**Product Use:** Acrylic cosmetic sealant for horizontal repairs to concrete or asphalt.**SECTION II - HAZARD IDENTIFICATION****Hazard-determining components of labeling:** Acrylic polymer**2.1 Classification of the substance or mixture**

Skin Irritant – Category 2

Eye Irritant – Category 2B

Acute Oral Toxicity – Category 4

Specific Target Organ Toxicity – Single Exposure – Category 3

2.2a Signal word Warning**2.2b Hazard Statements**

Causes skin and eye irritation

Harmful if swallowed

May cause respiratory irritation

CEMENT & CONCRETE PRODUCTS™**2.2c Pictograms****2.2d Precautionary statements**

Do not handle until all safety precautions have been read and understood.
Wear impervious gloves, such as nitrile. Wear eye protection, and protective clothing.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Use only in a well-ventilated area.
Do not breathe vapors.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If on skin (or hair): Remove immediately all contaminated clothing and wash before re-use. Rinse skin or hair with water.

If significant skin irritation or rash occurs: get medical advice or attention.

Immediately seek medical advice or attention if symptoms are significant or persist.

Dispose of contents/containers in accordance with all regulations.

2.3 Additional Information

2.3a HNOC – Hazards not otherwise classified: Not applicable

2.3b Unknown Acute Toxicity: None

2.3C WHMIS Classification

Class D2B – Skin/Eye Irritant

2.3d Label Elements According To WHMIS**Hazard Symbols****Signal Word**

**CEMENT & CONCRETE PRODUCTS™**

Warning

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components	CAS No.	% by Weight
Calcium Carbonate	1317-65-3	40-60
Acrylic Polymeric Resin	Not Hazardous	40-60
Water	7732-18-5	10-30
Titanium Dioxide	13463-67-7	1-2
Ethylene Glycol	107-21-1	1-2

Composition ranges provided due to batch-to-batch variability.
None of the constituents of this product are of unknown toxicity.

SECTION IV – FIRST AID MEASURES**4.1 Description of the first-aid measures****General information:**

After inhalation: Remove person to fresh air and keep comfortable for breathing.

After skin contact: Remove immediately all contaminated clothing and wash before re-use. Rinse skin or hair with water.

After eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing: Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms/effects, acute and delayed

Inhalation: May cause respiratory tract irritation.

Skin contact: Causes skin irritation.

Eye Contact: Causes eye irritation.

Ingestion: May be harmful if swallowed.

4.3 Indication of immediate medical attention and special treatment needed:

Immediately seek medical advice or attention if symptoms are significant or persist.

SECTION V - FIRE FIGHTING MEASURES

CEMENT & CONCRETE PRODUCTS™

5.1 Flammability of the Product: This is a water-based product and presents no particular fire or explosion hazard. Dry polymer film will burn. Product contains low levels of organic volatiles which may be emitted at elevated temperatures

5.2 Suitable extinguishing agents: Treat for surrounding material

5.3 Special hazards arising from the substance or mixture: None

5.3a Products of Combustion: Carbon monoxide, carbon dioxide and unknown hydrocarbons.

5.3b Explosion Hazards in Presence of Various Substances: Non-explosive in presence of shocks

SECTION VI – ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Wear personal protective equipment (See section VIII). Keep unprotected persons away.

6.2 Methods and material for containment and cleaning up:

Do not allow to enter sewers/ surface or ground water. Dispose of unwanted materials and containers properly in accordance with all regulations.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE**7.1 Handling**

Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace. Wear appropriate PPE (See section 8). Do not mix with other chemical products, except as indicated by the manufacturer. Do not get in eyes, on skin or clothing.

7.2 Storage

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep out of the reach of children

SECTION VIII – EXPOSURE CONTROL MEASURES / PERSONAL PROTECTION**8.1 Components with limit values that require monitoring at the workplace:**

Hazardous Components	CAS No.	PEL (OSHA) mg/M ³	TLV (ACGIH) mg/M ³
None			

8.2 Exposure Controls

Use ventilation adequate to keep exposures below recommended exposure limits.

8.3 General protective and hygienic measures

CEMENT & CONCRETE PRODUCTS™

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

8.3a Personal protective equipment**Protection of hands:**

Wear gloves of adequate length to offer appropriate skin protection from splashes. Nitrile, Butyl and PVC gloves have been found to offer adequate protection for incidental contact.

Eye protection:

Wear approved eye protection (properly fitted dust- or splash-proof chemical safety glasses).

Respiratory protection:

Respiratory protection is not required under intended use.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

General Information

Appearance	Form: Liquid Color: Various colors Odor: slight odor
pH-value at 20°C (68 °F):	8-9
Boiling point/Boiling range:	>212°F
Flash point:	>200°F (TCC)
Auto igniting:	Product is not self-igniting.
Vapor pressure at 21°C (70°F)	Not available
Density at 25°C (77 °F):	Acrylic Concrete Coating: 1.40 Masonry Waterproofing Coating: 1.53
Solubility in / Miscibility with	
Water:	Miscible
VOC content:	16 g/L, 1.1% by weight

SECTION X – STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal storage conditions.

10.3 Possibility of hazardous reaction

No dangerous reaction known under conditions of normal use.

CEMENT & CONCRETE PRODUCTS™**10.4 Thermal decomposition / conditions to be avoided**

No decomposition if used according to specifications.

10.5 Incompatible materials

Strong oxidizers, materials that react with water

10.6 Hazardous Decomposition or By-products

None known

SECTION XI – TOXICOLOGICAL INFORMATION

11.1 Exposure Routes: Skin contact, skin adsorption, eye contact, inhalation, or ingestion.

11.2 Symptoms related to physical/chemical/toxicological characteristics:

Inhalation: May cause respiratory tract irritation.

Skin contact: Causes skin irritation.

Eye Contact: Causes eye irritation.

Ingestion: Harmful if swallowed.

11.3 Delayed, immediate and chronic effects of short-term and long-term exposure
Short Term

Skin Corrosion/Irritation: Causes skin irritation

Serious Eye Damage/Irritation: Causes eye irritation

Respiratory Sensitization: Not available

Skin Sensitization: Not available

Specific Target Organ Toxicity-Single Exposure: (Category 3) May cause respiratory irritation.

Aspiration Hazard: Not available

Long Term

Carcinogenicity: Not available

Germ Cell Mutagenicity: Not available

Reproductive Toxicity: Not available

Specific Target Organ Toxicity- Repeated Exposure: Not available

Synergistic/Antagonistic Effects: Not available.

SECTION XII – ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or un-neutralized

12.2 Persistence and degradability

CEMENT & CONCRETE PRODUCTS™

No further relevant information available.

12.3 Bioaccumulative potential:

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Other Adverse Effects

No further relevant information available.

SECTION XIII – DISPOSAL CONSIDERATIONS**13.1 Waste Disposal Method**

The packaging and material may be land filled. This product is not classified as a hazardous waste under the authority of the RCRA (40CFR 261) or CERCLA (40CFR 117&302). Disposal must be made in accordance with local, state and federal regulations.

13.2 Other disposal considerations**Uncleaned packaging**

Recommendation: Disposal must be made in accordance with local, state and federal regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

SECTION XIV – TRANSPORT INFORMATION

	DOT (U.S.)	TDG (Canada)
UN-Number	Not Regulated	Not Regulated
UN proper shipping name	Not Regulated	Not Regulated
Transport Hazard Class(es)	Not Regulated	Not Regulated
Packing Group (if applicable)	Not Regulated	Not Regulated

14.1 Environmental hazards:

Not Available

14.2 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code

Not available

14.3 Special precautions for user

Do not handle until all safety precautions have been read and understood.

SECTION XV – OTHER REGULATORY INFORMATION

CEMENT & CONCRETE PRODUCTS™**15.1 Safety, Health and Environmental Regulations/Legislations specific for the chemical****Canada**

WHMIS Classification: Considered to be a D2B hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations and subject to the requirements of Health Canada's Workplace Hazardous Material Information (WHMIS). This document complies with the WHMIS requirements of the Hazardous Products Act (HPA) and the CPR.

15.2 US Federal Information**SARA 302/311/312/313 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302, 311, 312 or 313.

RCRA: Not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR §261 et seq.

CERCLA: Not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR §302.

Emergency Planning and Community Right to Know Act (SARA Title III): Not an extremely hazardous substance under Section 302 and is not a toxic chemical subject to the requirements of Section 313.

NTP: Not classified

OSHA Carcinogen: Not listed.

15.3 State Right to Know Laws**California Prop. 65 Components**

WARNING: This product does not contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

15.4 Global Inventories

DSL All components of this product are on the Canadian DSL list.

TSCA No.: All constituents are listed in the TSCA inventory.


15.5 NFPA Ratings

CEMENT & CONCRETE PRODUCTS™

NFPA Rating Explanation Guide

HEALTH HAZARD	FLAMMABILITY HAZARD
<ul style="list-style-type: none"> 4 = Can be lethal 3 = Can cause serious or permanent injury 2 = Can cause temporary incapacitation or residual injury 1 = Can cause significant irritation 0 = No hazard 	<ul style="list-style-type: none"> 4 = Will vaporize and readily burn at normal temperatures 3 = Can be ignited under almost all ambient temperatures 2 = Must be heated or high ambient temperature to burn 1 = Must be preheated before ignition can occur 0 = Will not burn
<ul style="list-style-type: none"> ALK = Alkaline ACID = Acidic COR = Corrosive OX = Oxidizing ☼ = Radioactive ☼☼ = Reacts violently or explosively with water ☼☼☼ = Reacts violently or explosively with water and oxidizing 	<ul style="list-style-type: none"> 4 = May explode at normal temperatures and pressures 3 = May explode at high temperature or shock 2 = Violent chemical change at high temperatures or pressures 1 = Normally stable. High temperatures make unstable 0 = Stable
SPECIAL HAZARD	INSTABILITY HAZARD

This chart for reference only - For complete specifications consult the NFPA 704 Standard



SECTION XVI – OTHER INFORMATION

Last Updated: February 18, 2016

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by

The QUIKRETE® Companies
 Phone (800) 282-5828
www.QUIKRETE.com

End of SDS