

Glidden Ultra-Hide 440  
Interior Latex Paint  
Semi-Gloss GP4-5110

1/15/2019

UH66-0300

PAGE 1

SECTION 1

PRODUCT IDENTIFIER UH66-0300 ULTRA-HIDE INTERIOR SEMI-GLOSS-BASE 2  
DATE OF PREPARATION JANUARY 3, 2012  
PRODUCT USE PROTECTIVE COATING

MANUFACTURED BY: AKZO NOBEL PAINTS LLC, 15885 WEST SPRAGUE ROAD,  
STRONGSVILLE, OHIO 44136, U.S.A  
AKZO NOBEL CANADA INC., 8200 KEELE STREET,  
CONCORD, ONTARIO L4K 2A5, CANADA.

EMERGENCY AND MSDS TELEPHONE NUMBER:  
1-800-545-2643

MSDS PREPARED BY: PRODUCT SAFETY AND COMPLIANCE DEPARTMENT  
AKZO NOBEL PAINTS LLC

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

	INGREDIENT	WT. %:
CHEMICAL NAME	ACRYLIC RESIN	1-5
COMMON NAME :	ACRYLIC RESIN	
CAS NUMBER:	CONFIDENTIAL	
CHEMICAL NAME	KAOLIN	1-5
COMMON NAME :	CLAY	
CAS NUMBER:	1332-58-7	
CHEMICAL NAME	TITANIUM OXIDE	1-5
COMMON NAME :	TITANIUM DIOXIDE	
CAS NUMBER:	13463-67-7	
CHEMICAL NAME	2-PROPENOIC ACID, BUTYL ESTER, POLYMER WITH ETHENYL ACETATE	20-30
COMMON NAME :	VINYL ACRYLIC LATEX	
CAS NUMBER:	25067-01-0	
CHEMICAL NAME	PROPANOIC ACID, 2-METHYL-, MONOESTER WITH 2,2,4-TRIMETHYL-1,3-PENTANEDIOL	1-5
COMMON NAME :	TEXANOL	

-----  
SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS  
-----

CAS NUMBER: 25265-77-4

CHEMICAL NAME WATER

60-70

COMMON NAME : WATER

CAS NUMBER: 7732-18-5

-----  
SECTION 3: HAZARDS IDENTIFICATION  
-----

## PRIMARY ROUTE(S) OF EXPOSURE

INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

## EFFECTS OF OVEREXPOSURE

## INHALATION

PROLONGED INHALATION MAY LEAD TO HEADACHE, NAUSEA, COUGHING,  
PNEUMOCONIOSIS.

## SKIN CONTACT

IRRITATION OF SKIN.

## EYE CONTACT

IRRITATION OF EYES.

## INGESTION

INGESTION MAY CAUSE MOUTH AND THROAT IRRITATION,  
GASTRO-INTESTINAL DISTURBANCES.

## MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

EYE, SKIN, RESPIRATORY DISORDERS, LUNG DISORDERS.

-----  
SECTION 4: FIRST-AID MEASURES  
-----

## INHALATION

REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED  
BREATHING.

GET EMERGENCY MEDICAL ATTENTION.

HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL  
HELP FOR ANY BREATHING DIFFICULTY.REMOVE TO FRESH AIR IF INHALATION CAUSES EYE WATERING,  
HEADACHES, DIZZINESS, OR OTHER DISCOMFORT.

---

**SECTION 4: FIRST-AID MEASURES**

---

**SKIN CONTACT** WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING.

**EYE CONTACT** FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

**INGESTION** IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

---

**SECTION 5: FIRE-FIGHTING MEASURES**

---

**FLASH POINT (SETA)** NONE LOWER EXPLOSIVE LIMIT NOT AVAILABLE  
UPPER EXPLOSIVE LIMIT NOT AVAILABLE

**FIRE EXTINGUISHING MEDIA**  
DRY CHEMICAL OR FOAM  
WATER FOG.  
CARBON DIOXIDE.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**  
CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.  
IN CLOSED TANKS, WATER OR FOAM MAY CAUSE FROTHING OR ERUPTION.

**FIRE FIGHTING PROCEDURES**  
WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS. FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

**HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS**  
CARBON MONOXIDE, CARBON DIOXIDE, ACRYLIC MONOMERS.

---

**SECTION 6 ACCIDENTAL RELEASE MEASURES**

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS.

ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. EVACUATE ALL UNNECESSARY PERSONNEL. PLACE COLLECTED MATERIAL IN PROPER CONTAINER. SPILLED MATERIAL IS EXTREMELY SLIPPERY. SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

---

**SECTION 7 HANDLING AND STORAGE**

---

**HANDLING AND STORAGE**

STORE BELOW 100F (38C). KEEP FROM FREEZING.

**OTHER PRECAUTIONS**

USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.

---

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

COMMON NAME : CLAY

CAS NUMBER: 1332-58-7

ACGIH (TWA) : 2 MG/M3 OSHA (TWA) : 5 MG/M3

COMMON NAME : TITANIUM DIOXIDE

CAS NUMBER: 13463-67-7

ACGIH (TWA) : 10 MG/M3 OSHA (TWA) : 10 MG/M3

**RESPIRATORY PROTECTION**

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS.

---

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

**VENTILATION** PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

**PERSONAL PROTECTIVE EQUIPMENT**

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES.  
IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING.

---

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	1.080
BOILING RANGE (F/C):	212-501/100-261	WEIGHT PER GALLON:	9.00/ 10.81IMP
%VOLATILE BY VOLUME:	71.39		
PHYSICAL STATE:	LIQUID	APPEARANCE	WHITE
SOLUBILITY IN WATER:	NOT AVAILABLE	PH:	NOT AVAILABLE

---

**SECTION 10: STABILITY AND REACTIVITY**

---

**UNDER NORMAL CONDITIONS**

STABLE  
SEE SECTION 5 FIRE FIGHTING MEASURES

**MATERIALS TO AVOID**

OXIDIZERS, ACIDS.  
STYRENE MONOMER.

**CONDITIONS TO AVOID**

ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT,  
FREEZING, SPARKS, OPEN FLAME.

-----  
 SECTION 10: STABILITY AND REACTIVITY  
 -----

HAZARDOUS POLYMERIZATION  
 WILL NOT OCCUR

-----  
 SECTION 11: TOXICOLOGICAL INFORMATION  
 -----

COMMON NAME : CLAY  
 CAS NUMBER: 1332-58-7  
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : TITANIUM DIOXIDE  
 CAS NUMBER: 13463-67-7  
 CARCINOGENICITY LISTED BY: NTP YES 2B IARC YES 2B OSHA NO ACGIH NO  
 LD50: 24.00 GM/KG ORL RAT  
 LC50: 6820.00 MG/M3/4HR IHL RAT

COMMON NAME : VINYL ACRYLIC LATEX  
 CAS NUMBER: 25067-01-0  
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : TEXANOL  
 CAS NUMBER: 25265-77-4  
 CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO  
 LD50: 3200.00 MG/KG ORL RAT  
 LD50:> 20.00 ML/KG SKN GPG

SUPPLEMENTAL HEALTH INFORMATION  
 NO ADDITIONAL EFFECTS ARE ANTICIPATED

CARCINOGENICITY THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC)  
 HAS CLASSIFIED TITANIUM DIOXIDE AS POSSIBLY CARCINOGENIC  
 TO HUMANS (GROUP 2B) BASED ON INADEQUATE EVIDENCE OF  
 CARCINOGENICITY IN HUMANS AND SUFFICIENT EVIDENCE OF  
 CARCINOGENICITY IN EXPERIMENTAL ANIMALS.

---

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

**REPRODUCTIVE EFFECTS** NO REPRODUCTIVE EFFECTS ARE ANTICIPATED  
**MUTAGENICITY** NO MUTAGENIC EFFECTS ARE ANTICIPATED  
**TERATOGENICITY** NO TERATOGENIC EFFECTS ARE ANTICIPATED

---

**SECTION 12: ECOLOGICAL INFORMATION**

---

NO ECOLOGICAL TESTING HAS BEEN DONE BY AKZO NOBEL PAINTS LLC ON THIS PRODUCT AS A WHOLE.

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

**WASTE DISPOSAL** DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

---

**SECTION 14: TRANSPORT INFORMATION**

---

**DOT** PAINT\*\*PROTECT FROM FREEZING\*\*  
**IMDG** NOT AVAILABLE  
**IATA** NOT AVAILABLE  
**TDG** NOT AVAILABLE

---

**SECTION 15: REGULATORY INFORMATION**

---

SARA SARA CERCLA HAZ AIR MARINE  
302 313 302.4 POLLUTANT POLTNT

THIS PRODUCT CONTAINS NO SARA 302, CERCLA 302.4 OR HAZARDOUS AIR POLLUTANT CHEMICALS. IT ALSO CONTAINS NO CHEMICALS WHICH ARE SUBJECT TO THE REPORTING REQUIREMENTS UNDER SARA 313.

---

**SECTION 15: REGULATORY INFORMATION**

---

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

---

**SECTION 16: OTHER INFORMATION**

---

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH AKZO NOBEL PAINTS LLC BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. AKZO NOBEL PAINTS LLC SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL.  
COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.



