

# SAFETY DATA SHEET

SAVOGRAN  
STRYPEEZE (DCM Free)  
Revision: 12/17/2018

SAVOGRAN Heavy Duty  
Striper Super Strip

Page 1 of 7

## 1. Product and Company Identification

Product Name : STRYPEEZE (DCM Free)  
Product Code : 230N  
Recommended Use: PAINT REMOVER

### Company Identification:


SAVOGRAN  
259 LENOX STREET  
PO BOX 130  
NORWOOD, MA 02062-0130  
Information Phone: 781-762-5400  
Emergency Phone: 800-424-9300  
Website Address: [www.savogran.com](http://www.savogran.com)

Synonyms: 01232,01233,01234,01235

## 2. Hazards Identification

### Classification:

Flammable liquids: Category 2/Eye irritation: Category 2A/Skin irritation: Category 2/Acute toxicity(oral): Category 3/Specific target organ toxicity(single exposure): Category 1/Aspiration toxicity: Category 1



### Label Hazard Statement and Precautionary Statements:

DANGER: POISON! EXTREMELY FLAMMABLE. May be fatal or cause blindness if swallowed. Skin and eye irritant. Keep away from sparks, heat and flames. Use outdoors if possible. If you must use indoors, open all windows and outside doors, use only with moving fresh air cross ventilation over the work area and across floor. Vapors flow along floors, under doors and may ignite explosively. Do not smoke. Before use shut off electricity to all outlets, switches, fans, motors, tools, stoves, heaters and appliances.

### Potential Health Effects:

#### Eye:

Eye contact can cause severe irritation, redness, tearing, blurred vision and may cause transient injury to cornea.

#### Skin:

# SAFETY DATA SHEET

SAVOGRAN  
STRYPEEZE (DCM Free)

Revision: 12/17/2018

Page 2 of 7

Short contact may cause slight reddening or no irritation. Prolonged or frequently repeated contact can cause irritation, defatting, dermatitis and may result in absorption of harmful amounts. Some ingredients in this product may be absorbed through intact skin and produce toxic effects similar to swallowing.

#### Ingestion:

Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Ingestion can cause blindness, nausea, vomiting, diarrhea, gastrointestinal irritation and death.

#### Inhalation:

Inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, headache, nausea, unconsciousness and asphyxiation.

#### Chronic Overexposure Information:

Intentional misuse by deliberately concentrating and inhaling the product may be harmful or fatal. Reports have associated repeated and prolonged overexposure to solvents with permanent brain, nervous system, liver and kidney damage.

#### Teratology and Reproduction Information:

Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

#### Aggravation of Pre-Existing Conditions:

Pre-existing upper respiratory and lung diseases such as, but not limited to, bronchitis, emphysema and asthma. Pre-existing skin diseases such as, but not limited to, rashes and dermatitis.

#### OSHA Hazard Communication Standard:

This product is defined as hazardous by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### 3. Composition/Information on Ingredients

Component	CAS#	% by Wt.
* TOLUENE		
ACGIH 20 ppm TWA, A4	108-88-3	25% - 30%
OSHA 200 ppm TWA/300 ppm CEILING		
* METHANOL		
ACGIH (SKIN)/OSHA 200 ppm TWA	67-56-1	20% - 25%
ACGIH 250 ppm STEL-SKIN		
ACETONE		
ACGIH 500 ppm TWA/750 ppm STEL, A4	67-64-1	20% - 25%
OSHA 1000 ppm TWA		
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	10% - 15%
OSHA 100 ppm TWA		
N,N-DIMETHYL 9-DECENAMIDE	1356964-77-6	10% - 15%
NO EXPOSURE LIMITS LISTED		

# SAFETY DATA SHEET

SAVOGRAN  
STRYPEEZE (DCM Free)

Revision: 12/17/2018

Page 3 of 7

PARAFFIN WAX  
ACGIH 2 mg/m<sup>3</sup> TWA (fume)

8002-74-2 0.1% - 5%

## 4. First Aid Measures

---

**Eyes:**  
Flood with plenty of water with eye lids held open for at least 15 minutes and get medical attention promptly.

**Skin:**  
Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

**Ingestion:**  
Immediately give 1 or 2 glasses of water and call physician, hospital emergency room or poison control center for way to induce vomiting. Get medical attention promptly. Never give anything by mouth to an unconscious person. Aspiration of material into lungs can cause chemical pneumotitis which can be fatal.

**Inhalation:**  
If illness occurs, remove patient to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, start artificial respiration. Call physician immediately.

**Note to Physicians:**  
This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.

## 5. Fire Fighting Measures

---

**Flammable Properties:**  
DANGER! EXTREMELY FLAMMABLE. Keep away from heat, sparks, flame and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated.

**Hazardous Combustion Products:**  
May form carbon dioxide and carbon monoxide, various hydrocarbons.

**Extinguishing Media:**  
Water fog, regular foam, carbon dioxide or dry chemical.

**Firefighting Procedures:**  
Wear self-contained breathing apparatus with full face piece operated in pressure-demand or other positive pressure mode. Straight water steam will spread fire. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.

# SAFETY DATA SHEET

SAVOGRAN  
STRYPPEZE (DCM Free)

Revision: 12/17/2018

Page 4 of 7

---

## 6. Accidental Release Measures

---

### Small Spill:

Wipe or scrape up any material. Wash area thoroughly with detergent and water; ventilate adequately with good fresh air movement at floor level.

### Large Spill:

Wear proper protective equipment. Stop spill at source, dike area of spill to keep from spreading and keep out of ground water and streams. Transfer material to metal containers. Absorb remainder with sand, clay, earth, floor absorbent or other material and shovel into containers. Then wash area thoroughly with water and detergent. Ventilate adequately with good fresh air movement at floor level. Do not restart pilot lights or operate electrical devices or other sources of sparks, flames or heat until all vapors (odors) are gone.

### Environmental Precautions:

Prevent spills from entering storm sewers or drains and contact with soil.

### Methods/Materials for Containment and Cleaning Up:

Eliminate all ignition sources. Runoff may create fire or explosion hazard in sewer system. Absorb on fire retardant, liquid-absorbing material. Shovel up and dispose of at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal.

---

## 7. Handling and Storage

---

### Handling:

Do not breathe material. Keep container closed. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor and liquid), all hazard precautions given in the data sheet must be observed. All five-gallon pails and larger metal containers should be grounded and/or bonded when material is transferred.

### Storage:

Store in cool place, out of hot sun and below 90F. All containers are subject to damage in storage and transit. Damaged containers may start leaking immediately or at a later time. Do not store flammable materials in areas with widely fluctuating temperatures and do not store where vapors may come in contact with flames, sparks, or heat. Flammable materials should not be stored in below ground areas that cannot be adequately ventilated at floor level. Do not use cutting or welding torches near full or empty containers. Closed containers may explode if exposed to extreme heat. Never use internal gas or air pressure to remove contents from a container. Emptied containers may retain product residues (e.g. vapor and liquid or solids); Therefore all precautions given in this sheet must be observed until a container is thoroughly cleaned or destroyed. All containers must be completely drained, (less than one inch of material in the bottom of 55 gallon container) before disposal. If possible emptied container of 55 gallons or more should be given to reconditioner for cleaning.

# SAFETY DATA SHEET

SAVOGRAN  
STRYPPEZE (DCM Free)

Revision: 12/17/2018

Page 5 of 7

---

## 8. Exposure Controls/Personal Protection

---

Airborne Exposure Limits: See Section 3

### Engineering Controls:

The vapors are heavier than air and due care must be exercised to prevent them from collecting in low, unventilated areas. Vapors may travel along the floor (even under and around closed doors). Adequate ventilation must be provided with good fresh air movement at floor level by normal cross ventilation or preferably good explosion proof exhaust fans. Limit concentration of any solvent in air to exposure guidelines.

### Personal Protective Equipment:

#### Respiratory Protection:

For known vapor concentrations above the occupational exposure guidelines, use NIOSH approved organic vapor respirator.

#### Skin Protection:

Neoprene, butyl or safety 4H laminate glove.

#### Eye Protection:

Chemical goggles or safety glasses with side shield. Eye wash stations with safety showers should be readily available. Plastic glasses may be dissolved by paint removers and other solvents.

---

## 9. Physical and Chemical Properties

---

Boiling Point: 133.0  
Melting Point: NO DATA  
Freezing Point: NO DATA  
Vapor Pressure: 92mmHg20C  
Vapor Density: Heavier than air  
Solubility in Water: Appreciable  
Evaporation Rate: LESS THAN ETHER  
Flash Point: 18.5F

Method: SETAFLASH CLOSED CUP (ASTM D3828)

Lower explosive limit: NO DATA  
Upper explosive limit: NO DATA  
Autoignition Temperature: NO DATA  
Specific Gravity: .833  
pH(1% in H2O): 6-7  
Odor: Aromatic  
Appearance: Thick orange liquid

---

## 10. Stability and Reactivity

---

# SAFETY DATA SHEET

SAVOGRAN  
STRYPEEZE (DCM Free)

Revision: 12/17/2018

Page 6 of 7

---

Chemical Stability (Conditions to Avoid): Stable

Incompatibility:

Strong oxidizing agents (e.g. nitric acid, permanganates, etc.)  
strong alkalis (e.g. NaOH ammonia, etc.), strong acids (e.g. HCl, sulfuric,  
etc.) may react with aluminum.

Hazardous Decomposition Products:

Carbon dioxide and carbon monoxide, various hydrocarbons.

Hazardous Polymerization: Will not occur.

## **11. Toxicological Information**

---

Acute:

This product has not been tested as a whole.

Subchronic:

This product has not been tested as a whole.

Chronic/Carcinogenicity:

Not listed by ACGIH, IARC, NIOSH, NTP or OSHA

Routes of Exposure:

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

## **12. Ecological Information**

---

Environmental Fate: This product has not been tested as a whole.

## **13. Disposal Considerations**

---

Waste Disposal Method:

Removers cannot be neutralized for disposal into a sewer. Solvents must not be dumped on the ground or be allowed to contaminate ground water, streams, drinking water sources or other bodies of water. Solids collected from stripping should be screened out. Recovered remover, if not contaminated with other solvents or water, may be recycled in the system. Dispose of contaminated remover as spent solvent to a licensed reclaimer. Comply with all local, state, and federal regulations.

## **14. Transport Information**

---

Land Transport (DOT):

Gallon or smaller, Limited Quantity; Five gallon drum or larger, UN1263/paint related material/3/PGII- Flammable

# SAFETY DATA SHEET

SAVOGRAN  
STRYPREEZE (DCM Free)

Revision: 12/17/2018

Page 7 of 7

## 15. Regulatory Information

---

### U.S. Federal Regulations:

TSCA: The intentional ingredients of this product are listed.

OSHA: The intentional regulated ingredients of this product are listed.

CERCLA: SARA Hazard Category: Immediate/Fire

Section 313: This product contains chemicals (Marked \* in section 3) which are subject to reporting requirements of Section 313 of Title III of The Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372

Reportable Quantity: Product Components (Toluene-1000lb; Acetone-5000lb; Methanol-5000lb)

State Regulations: New Jersey RTK Label Information: Toluene, 108-88-3, Acetone, 67-64-1, Methanol, 67-56-1, Distillates (Petroleum), 64742-47-8

Pennsylvania RTK Label Information: Benzene, Methyl-, 108-88-3, Acetone, 67-64-1, Methanol, 67-56-1, Distillates (Petroleum), 64742-47-8

WARNING: This product can expose you to chemicals including Toluene and Methanol which are known to the State of California to cause birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Volatile Organic Compounds: 50% by wt.; 405 g/l; 3.47 lbs/gallon

## 16. Other Information:

---

NFPA Ratings: 2, 3, 0

Manufacturer Disclaimer: Judgement of potential hazards of this product is based on information available about individual components listed under section 3 - Ingredients. Direct testing of mixture has not been done. Flash point has been tested. Information given herein is believed to be accurate and is given in good faith. However, no warranty either expressed or implied is made. It is strongly suggested that users confirm in advance of need that the information is current and applicable to their situations.