


10/19/21

	<i>recommended for Honda, Hyundai, Nissan, Subaru</i>
SAFETY DATA SHEET	Revision Date: 05/19/2017
	Print Date: 6/2/2017
	SDS Number: 000000141647
Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50 Antifreeze Coolant ™ Trademark, Valvoline or its subsidiaries, registered in various countries 675130	Version: 1.3 <i>Zerex Asian Vehicle Formula Antifreeze/Coolant</i> <i>5 year/150,000 miles Silicate & Borate free</i> <i>Valvoline 50/50 Prediluted Antifreeze Do Not Add water</i>

29 CFR 1910.1200 (OSHA HazCom 2012)
SECTION 1. PRODUCT AND COMPANY IDENTIFICATION



Product identifier
Trade name : Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50 Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various countries

Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL	Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification
Acute toxicity (Oral) : Category 4

Specific target organ systemic toxicity - repeated exposure (Oral) : Category 2 (Kidney, Liver)

GHS label elements
Hazard pictograms :  

Signal Word : Warning

Hazard Statements : Harmful if swallowed.
May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
675130

Do not eat, drink or smoke when using this product.

Response:

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Get medical advice/ attention if you feel unwell.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	48.9793
DIETHYLENE GLYCOL	111-46-6	Acute Tox. 4; H302 STOT RE 2; H373	2.4502
SODIUM BENZOATE	532-32-1	Eye Irrit. 2A; H319	2.4159

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.



SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 675130

- In case of eye contact : Flush eyes with water as a precaution.
 Remove contact lenses.
 Protect unharmed eye.
 If eye irritation persists, consult a specialist.

- If swallowed : Obtain medical attention.
 Rinse mouth with water.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.

- Most important symptoms and effects, both acute and delayed : Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.

 Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
 stomach or intestinal upset (nausea, vomiting, diarrhea)
 irritation (nose, throat, airways)
 Cough
 pain in the abdomen and lower back
 cyanosis (causes blue coloring of the skin and nails from lack of oxygen)
 lung edema (fluid buildup in the lung tissue)
 acute kidney failure (sudden slowing or stopping of urine production)
 Convulsions
 Harmful if swallowed.

- Notes to physician : This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene



SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 675130

glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Alcohols
 Aldehydes
 carbon dioxide and carbon monoxide
 ethers
 toxic fumes
 Hydrocarbons
 Sodium oxides
- Specific extinguishing methods :

 Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Persons not wearing protective equipment should be excluded



SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 675130

- protective equipment and emergency procedures : from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
 Do not smoke.
 Container hazardous when empty.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	C	100 mg/m3 Aerosol only	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0
		C	40 ppm 100 mg/m3 Vapour	CAL PEL
DIETHYLENE GLYCOL	111-46-6	TWA	10 mg/m3	US WEEL


SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
675130

Hazardous components without workplace control parameters

Components	CAS-No.
SODIUM BENZOATE	532-32-1

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

: Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : pink

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 212 °F / 100 °C
(1,013.333333 hPa)
Calculated Phase Transition Liquid/Gas


SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 675130

Flash point : > 250 °F / > 121 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 15.3 %(V)
GLP: Calculated Explosive Limit

Lower explosion limit : 3.2 %(V)
GLP: Calculated Explosive Limit

Vapour pressure : 23.3333333 hPa (20 °C)
Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 1.0827 g/cm3 (15.6 °C)

Solubility(ies)
 Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-
 octanol/water : No data available

Thermal decomposition : No data available

Viscosity
 Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous
 reactions : Product will not undergo hazardous polymerization.

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
675130

Conditions to avoid : excessive heat
Exposure to moisture

Incompatible materials : Acids
Aldehydes
Alkali metals
Alkaline earth metals
Bases
iron salts
strong alkalis
Strong oxidizing agents
Sulphur compounds

Hazardous decomposition products : Alcohols
Aldehydes
carbon dioxide and carbon monoxide
ethers
Hydrocarbons
Organic acids
Sodium oxides
ketones

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity
Harmful if swallowed.

Product:

Acute oral toxicity :
Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be considered toxic by ingestion.

Acute dermal toxicity : Remarks: Skin absorption of this material (or a component) may be increased through injured skin.

Components:**ETHYLENE GLYCOL:**

Acute oral toxicity : LD0 (Human): Estimated 1.56 g/kg

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
675130

Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

DIETHYLENE GLYCOL:

Acute oral toxicity : LD50 (Human): Expected 1,120 mg/kg
Target Organs: Kidney

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

SODIUM BENZOATE:

Acute oral toxicity : LD50 (Rat, male and female): 3,450 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 12.2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Remarks: Information given is based on data obtained from similar substances.

Skin corrosion/irritation

Not classified based on available information.

Components:**ETHYLENE GLYCOL:**

Species: Rabbit

Result: No skin irritation

DIETHYLENE GLYCOL:

Species: Human

Result: Slight, transient irritation

SODIUM BENZOATE:

Result: Slight, transient irritation

Serious eye damage/eye irritation

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
675130

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

ETHYLENE GLYCOL:

Result: Slight, transient irritation

DIETHYLENE GLYCOL:

Species: Rabbit

Result: Slight, transient irritation

SODIUM BENZOATE:

Species: Rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

DIETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Genotoxicity in vitro

: Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

DIETHYLENE GLYCOL:

Genotoxicity in vitro

: Test Type: Ames test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
675130

: Test species: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 479
Result: negative
GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Test species: Mouse
Method: OECD Test Guideline 474
Result: negative
GLP: yes

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:**ETHYLENE GLYCOL:**

Exposure routes: Ingestion

Target Organs: Kidney, Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

DIETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Experience with human exposure**Components:****DIETHYLENE GLYCOL:**

Liver

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Ecotoxicology Assessment

Acute aquatic toxicity

: Not classified based on available information.

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
675130

Chronic aquatic toxicity : Not classified based on available information.

Components:**ETHYLENE GLYCOL:**

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 -
13,000 mg/l
End point: Growth inhibition
Exposure time: 7 Days

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l
Exposure time: 7 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l
Exposure time: 7 d

DIETHYLENE GLYCOL:

Toxicity to fish : LC50 (Fathead minnow (Pimephales promelas)): 75,210 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : LC50 (Water flea (Daphnia magna)): > 10,000 mg/l
Exposure time: 24 h
Test Type: static test
Method: DIN 38412

SODIUM BENZOATE:

Toxicity to fish : LC50 (Fathead minnow (Pimephales promelas)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: Static
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : LC50 (Water flea (Daphnia magna)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: Static
Remarks: Mortality

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
675130

Persistence and degradability**Components:****ETHYLENE GLYCOL:**

Biodegradability

: Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 10 d
Method: OECD Test Guideline 301

DIETHYLENE GLYCOL:

Biodegradability

: Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

SODIUM BENZOATE:

Biodegradability

: Result: Readily biodegradable.
Biodegradation: 88 %
Exposure time: 28 d
Method: OECD Test Guideline 301

No data available

Bioaccumulative potential**Components:****ETHYLENE GLYCOL:**

Bioaccumulation

: Species: Crayfish (Procambarus)
Bioconcentration factor (BCF): 0.27
Exposure time: 61 d
Concentration: 1000 mg/l
Method: Flow through

Partition coefficient: n-
octanol/water

: log Pow: -1.36

DIETHYLENE GLYCOL:

Bioaccumulation

: Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 100

Partition coefficient: n-
octanol/water

: log Pow: -1.47

No data available

Mobility in soil**Components:**

No data available

Other adverse effects

No data available

Product:

Additional ecological : No data available

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
675130

information

Components:**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods****General advice**

: Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and
federal regulations.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste
handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International transport regulations****REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
675130

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant

no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ETHYLENE GLYCOL	107-21-1	5000	10208

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard
Acute Health Hazard

SARA 313



SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 675130

ETHYLENE GLYCOL 107-21-1 48.97 %

California Prop 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/19/2017

<p>NFPA:</p> <p style="text-align: center;">Flammability</p> <div style="display: flex; align-items: center; justify-content: center;"> <div style="writing-mode: vertical-rl; transform: rotate(180deg); margin-right: 10px;">Health</div>  <div style="writing-mode: vertical-rl; margin-left: 10px;">Instability</div> </div> <p style="text-align: center;">Special hazard.</p>	<p>HMIS III:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: black; color: white; padding: 5px;">HEALTH</td> <td style="text-align: center; padding: 5px;">1*</td> </tr> <tr> <td style="background-color: black; color: white; padding: 5px;">FLAMMABILITY</td> <td style="text-align: center; padding: 5px;">1</td> </tr> <tr> <td style="background-color: black; color: white; padding: 5px;">PHYSICAL HAZARD</td> <td style="text-align: center; padding: 5px;">0</td> </tr> </table> <p style="font-size: small;">0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	1*	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	1*						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification
 Combustible Liquid Class III


SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
Antifreeze Coolant
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
675130

Full text of H-Statements

H302 Harmful if swallowed.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure
if swallowed.

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for
labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether
originating with the company or not. Recipients are advised to confirm in advance of need that the
information is current, applicable, and suitable to their circumstances. This SDS has been
prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data
sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement


SAFETY DATA SHEET

Revision Date: 05/19/2017

Print Date: 6/2/2017

SDS Number: 000000141647

Version: 1.3

Zerex™ ASIAN VEHICLE LONG-LIFE/HOAT FORMULA 50/50
 Antifreeze Coolant
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 675130

PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System