

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015




Product identifier

- **Trade name:** Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding
- **Product number:**
 - Specification: A5.18
 - Classification: E70C-6M, ER70S-2, ER70S-2 (Copper Free), ER70S-3, ER70S-4, ER70S-6, ER70S-6 (Copper Free)
 - Carbon steel electrodes and rods for gas shielded arc welding
- **Relevant identified uses of the substance or mixture and uses advised against:**
 - For professional use only. Use according to manufacturer's specification.
- **Product description** Carbon steel electrodes and rods for gas shielded arc welding.
- **Application of the substance / the mixture:** Industry specific application.

Details of the supplier of the safety data sheet

- **Supplier:**
 - SOWESCO I, LLC
 - 9384 Wallisville Road
 - Houston, TX 77013
 - Telephone: 800-856-9353
- **Emergency telephone number:** 713-688-9353

Gas shield CARBON steel
SOLID ARC Welding
Electrodes



Classification of the substance or mixture:



GHS08 Health hazard

- Carc. 1A H350 May cause cancer.
- STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

- Eye Dam. 1 H318 Causes serious eye damage.



GHS07

- Skin Irrit. 2 H315 Causes skin irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- STOT SE 3 H335 May cause respiratory irritation.

Label elements:

- **GHS label elements**
 - The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS05



GHS07



GHS08

- **Signal word:** Danger

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding**Hazard-determining components of labeling:**

Iron
Lithium
Silica
Nickel
Titanium Dioxide

Hazard statements:


Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause cancer.
Causes damage to organs through prolonged or repeated exposure.

Precautionary statements:

Do not handle until all safety precautions have been read and understood.
Obtain special instructions before use.
Do not eat, drink or smoke when using this product.
Do not breathe dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Wear respiratory protection.
Wear protective gloves/protective clothing/eye protection/face protection.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Take off contaminated clothing and wash it before reuse.
If in eyes: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
If on skin: Wash with plenty of water.
If skin irritation or rash occurs: Get medical advice/attention.
If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a poison center/doctor if you feel unwell.
If exposed or concerned: Get medical advice/attention.
If experiencing respiratory symptoms: Call a poison center/doctor.
Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

19 percent of the mixture consists of ingredient(s) of unknown toxicity.

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 2
Fire = 0
Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = *2
Fire = 0
Reactivity = 0

Hazard(s) not otherwise classified (HNOC): None known

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding**Chemical characterization: Mixtures**

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous Components:

CAS: 7439-89-6 RTECS: NO 4565500	Iron ⚠Flam. Sol. 2, H228; ⚠Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320; Combustible Dust	85-99%
CAS: 13463-67-7	Titanium Dioxide ⚠Carc. 2, H351; ⚠Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0-10%
CAS: 7440-39-3 RTECS: CQ 8370000	Barium ⚠Water-react. 2, H261	0-10%
CAS: 1317-95-9	Silica ⚠Carc. 1A, H350; ⚠STOT SE 3, H335	0-3%
CAS: 7439-93-2 RTECS: OJ 5540000	Lithium ⚠Water-react. 1, H260; ⚠Skin Corr. 1B, H314	0-9%
CAS: 7429-90-5 RTECS: BD 0330000	Aluminium ⚠Flam. Sol. 2, H228	0-5%
CAS: 7440-21-3	Silicon ⚠Flam. Sol. 2, H228; ⚠Acute Tox. 4, H302; Eye Irrit. 2B, H320	0-1.5%
CAS: 7440-02-0	Nickel ⚠Carc. 2, H351; STOT RE 1, H372; ⚠Skin Sens. 1, H317	0-3%
CAS: 7631-86-9	Silicon Dioxide ⚠Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	0-2%
CAS: 1344-28-1 RTECS: BD 1200000	Aluminum Oxide ⚠STOT SE 3, H335	0-1%
CAS: 1309-48-4	Magnesium Oxide ⚠Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0-1%
CAS: 7440-50-8 RTECS: GL 5325000	Copper ⚠STOT SE 3, H335; Aquatic Chronic 4, H413	0-1%
CAS: 7439-98-7 RTECS: QA 4680000	Molybdenum	0-1%
CAS: 7440-44-0 RTECS: FF 5250100	Carbon	0-1%
CAS: 7440-67-7 RTECS: ZH 7070000	Zirconium ⚠Pyr. Sol. 1, H250; Water-react. 1, H260	0-1%
CAS: 7440-32-6 RTECS: XR 1700000	Titanium ⚠Skin Sens. 1, H317; Eye Irrit. 2B, H320	0-0.5%
CAS: 7439-96-5 RTECS: OO 9275000	Manganese ⚠Pyr. Sol. 1, H250; Water-react. 1, H260	0-5%
CAS: 7440-03-1 RTECS: QT9900000	Niobium ⚠Flam. Sol. 1, H228; Combustible Dust	0-0.3%
CAS: 7440-62-2 RTECS: YW 1355000	Vanadium	0-0.3%
CAS: 1317-61-9	Iron Oxide	0-12%

Additional information

Note: Certain chemical constituents listed in section 3 may vary depending upon the Classification of the Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding products.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding**Description of first aid measures**

- **General information:**

Symptoms of poisoning may occur after several hours; therefore medical observation is advised for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness, place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.

- **After eye contact:**

Do NOT rub eyes. Immediately rinse opened eye(s) for at least 15 minutes under running water, lifting upper and lower lids occasionally. If symptoms persist, consult a physician.

- **After swallowing:**

Rinse out mouth and then drink plenty of water. Do not induce vomiting without medical advice. If swallowed and symptoms occur, consult a doctor.

Information for doctor

- **Most important symptoms and effects, both acute and delayed:**

No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

**Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

Amorphous or crystalline silicon both react exothermically when heated with alkali-metal carbonates attaining incandescence and evolving carbon monoxide. Mixtures of silicon, aluminum, and lead explode when heated. If incinerated, product will release the following toxic fumes: Oxides of silicon, aluminum, magnesium, manganese, iron, copper, molybdenum, carbon, titanium, nickel, niobium, vanadium, barium, lithium, and zirconium, and fluorides and ozone.

Advice for firefighters

- **Protective equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

Additional information

At temperatures above 200 °C, zirconium reacts exothermically with the following: fluorine, chloride, bromide, iodine, halocarbons, carbon tetrachloride, carbon, tetra fluoride and Freon's.

These items are not reactive, flammable, or explosive and essentially not hazardous at ambient temperatures. Welding arcs and sparks can ignite combustibles and flammable products. If involved in a fire, these products may generate irritating aluminum fumes and a variety of metal oxides. Emergency responders must wear personal protection equipment suitable for the situation. Use the extinguishing media recommended for the burning materials and fire situation. See ANSI Z49.1 "Safety in Welding and Cutting" and "Safe Practices" Code: SP, published by the American Welding Society.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding**Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures:**
 - Ensure adequate ventilation.
 - Wear protective equipment.
 - Keep unprotected persons away.
 - Avoid contact with skin, eyes and clothing.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 - Ensure adequate ventilation.
 - Pick up mechanically.
 - Dispose contaminated material as waste according to section 13.
 - Dispose of the collected material according to regulations.
- **Reference to other sections:**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

Waste disposal considerations**Handling**

- **Precautions for safe handling:**
 - Open and handle receptacle with care.
 - Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
 - Keep protective respiratory device available.

Storage

- **Conditions for safe storage, including any incompatibilities:**
 - Store away from strong acids, strong bases, strong oxidizing agents and strong reducing agents.
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

Exposure controls/personal protection**Additional information about design of technical systems**

No further data; see section 7.

Control parameters

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in air below TLV & PEL limits.

Components with occupational exposure limits:**13463-67-7 Titanium Dioxide**

PEL	Long-term value: 15* mg/m ³ *total dust
REL	See <u>Pocket Guide App. A</u>
TLV	Long-term value: 10 mg/m ³ withdrawn from NIC

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding**7440-39-3 Barium**

- PEL Long-term value: 0.5 mg/m³
as Ba
- REL Long-term value: 0.5 mg/m³
as Ba and soluble compounds
- TLV Long-term value: 0.5 mg/m³
as Ba

1317-95-9 Silica

- PEL see Quartz listing
- REL Long-term value: 0.05* mg/m³
*respirable dust; See Pocket Guide App. A
- TLV TLV withdrawn

7429-90-5 Aluminium

- PEL Long-term value: 15*; 15** mg/m³
*total dust; ** respirable fraction
- REL Long-term value: 10* 5** mg/m³
as Al; *total dust **respirable/pyro powd./welding f.
- TLV Long-term value: 1* mg/m³
as Al; *as respirable fraction

7440-21-3 Silicon

- PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction
- REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction
- TLV TLV withdrawn

7440-02-0 Nickel

- PEL Long-term value: 1 mg/m³
- REL Long-term value: 0.015 mg/m³
as Ni; See Pocket Guide App. A
- TLV Long-term value: 1.5* mg/m³
elemental, *inhalable fraction

7631-86-9 Silicon Dioxide

- ACGH Short-term value: 3 mg/m³
Long-term value: 10 mg/m³
- IDLH Short-term value: 3000 mg/m³
Long-term value: 4 E mg/m³
IDLH: Immediately dangerous to life or health
- TWA Short-term value: 6 mg/m³
Long-term value: 4 E mg/m³

1344-28-1 Aluminium Oxide

- PEL Long-term value: 15*; 15** mg/m³
*total dust ** respirable fraction
- REL Long-term value: 10* 5** mg/m³
as Al; *total dust**respirable/pyro powd./welding f.
- TLV Long-term value: 1* mg/m³
as Al; *as respirable fraction

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding**1309-48-4 Magnesium Oxide**PEL Long-term value: 15* mg/m³
fume; *total particulateTLV Long-term value: 10* mg/m³
*as inhalable fraction**7440-50-8 Copper**PEL Long-term value: 1* 0.1** mg/m³
as Cu; *dusts and mists **fumeREL Long-term value: 1* 0.1** mg/m³
as Cu; *dusts and mists **fumeTLV Long-term value: 1* 0.2** mg/m³
as Cu; *dusts and mists **fume**7439-98-7 Molybdenum**PEL Long-term value: 15* mg/m³
total dustTLV Long-term value: 10 3** mg/m³
as Mo; *inhalable fraction **respirable fraction**7440-44-0 Carbon**PEL Short-term value: 10 A mg/m³
Long-term value: 5 A mg/m³**7440-67-7 Zirconium**PEL Long-term value: 5 mg/m³
as ZrREL Short-term value: 10 mg/m³
Long-term value: 5 mg/m³
as ZrTLV Short-term value: 10 mg/m³
Long-term value: 5 mg/m³
as Zr**Additional information:** The lists that were valid during the creation of this SDS were used as basis.**Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing and wash before reuse.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

Breathing equipment:

Suitable respiratory protective device recommended.

Use NIOSH approved or equivalent fume respirator or air supplied respirator when welding, brazing, cutting, grinding, or soldering in a confined space or general work area where local exhaust and/or ventilation does not keep exposure below the limits outlined in section 8. Monitor the air quality inside the welder's helmet, and/or worker's breathing zone to determine if a respirator is required and the type needed.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding**Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/the chemical mixture. Select glove material based on penetration times, rates of diffusion and degradation.

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Eye protection:

Wear a helmet or face shield with a filter lens around shade number 14. Adjust if needed by selecting the next lighter or darker shade number. See ANSI/ASC Z49.1 Section 4.2 or publication F2.2. Shield other workers by providing screens and flash goggles.

Body protection:

Wear approved head, hand, and body protection, which help to prevent injury from radiation, sparks, and electrical shock. This would include wearing welder's gloves and a protective face shield and may include arm protectors, apron, hats, shoulder protection, as well as dark, non-synthetic, substantial clothing. See ANSI Z49.1. Welders should be trained not to allow electrically live parts to contact the skin or wet clothing and gloves. The welders should insulate themselves from the work and ground and should not touch live electrical parts. Welders should not wear short sleeve shirts or short pants.

9 Physical and chemical properties**Information on basic physical and chemical properties****General Information****Appearance:****Form:**

Metal Cored Wire/Rod or Solid Wire/Rod

Color:

Copper or silver/gray metallic color

Odor:

Odorless until used

Odor threshold:

Not determined.

pH-value:

Not applicable.

Change in condition**Melting point/Melting range:**

Not determined.

Boiling point/Boiling range:

Not determined.

Flash point:

Not applicable.

Flammability (solid, gaseous):

Not determined.

Ignition temperature:

Not determined.

Decomposition temperature:

Not determined.

Auto igniting:

Product is not self-igniting.

Danger of explosion:

Product does not present an explosion hazard.

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding

· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not applicable.
· Density:	
Relative density:	Not determined.
Vapor density:	Not applicable.
· Evaporation rate:	Not applicable.
· Solubility in / Miscibility with Water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Organic solvents:	0.0 %
Solids content:	100.0 %
· Other information:	No further relevant information available.

Reactivity and Chemical Stability

- **Reactivity:** Stable under normal conditions.
- **Chemical stability:** Stable under normal conditions.
- **Possibility of hazardous reactions:** Contact with acids or strong bases may cause generation of gas.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** Strong acids, strong bases, strong oxidizing agents and strong reducing agents.
- **Hazardous decomposition products:**

Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the processes and procedures followed, and the welding consumables used. Other conditions that also influence the composition and quantity of fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating, or galvanizing), the number of welders in operation and the volume of the work area, the quality and amount of ventilation, the position of the welder's head with respect to the fume plume, and the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing procedures). When the electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in section 8. Fume and gas decomposition, and not the ingredients in the electrode, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration. Also, new compounds not in the electrodes may form. The known gases and fumes that may form during welding or cutting and their exposure limits are noted in the list in section 11 below. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in section 8, plus those from the base metal and coating, etc. as noted above. Chlorinated solvents may be decomposed into toxic gases such as phosgene.

It is understood, however, that the elements and/or oxides to be mentioned are virtually always present as complex oxides and not as metals (See "Characterization of Arc Welding Fume", from the American Welding Society). The elements or oxides listed section 8 correspond to the ACGIH categories found in "Threshold Limit Values for Chemical Substances and Physical Agents" listed in section 8. Some products will also contain: Oxides of silicon, aluminum, magnesium, manganese, iron, copper, molybdenum, carbon, titanium, nickel, niobium, vanadium, barium, lithium, and zirconium, and fluorides and ozone. Some elements or compounds may exceed their PELs/TLVs before the total fumes exceed 5mg/m³.

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding

- NICKEL, NICKEL COMPOUNDS may lung fibrosis or pneumoconiosis. Studies of nickel refinery workers indicated a higher incidence of lung and nasal cancers.
- SILICA (respirable crystalline silica) overexposure may result in silicosis. Respirable crystalline silica is a known human carcinogen. SILICA (amorphous) long term overexposure may cause pneumoconiosis. Noncrystalline forms of silica (amorphous silica) are considered to have little fibrotic potential.
- TITANIUM DIOXIDE may cause pulmonary irritation and slight fibrosis.

• **Acute toxicity:****LD/LC50 values that are relevant for classification:****7439-89-6 Iron**

Oral LD50 7500 mg/kg (rat)

13463-67-7 Titanium Dioxide

Oral LD50 >10000 mg/kg (rat)

Dermal LD50 >10000 mg/kg (rabbit)

Inhalative LC50/4 h >6.82 mg/l (rat)

7429-90-5 Aluminium

Oral LD50 >2000 mg/kg (rat)

Inhalative LC50/4 h 888 mg/l (rat)

7440-21-3 Silicon

Oral LD50 3160 mg/kg (rat)

7631-86-9 Silicon Dioxide

Oral LD50 10000 mg/kg (rat) (OECD 401)

Dermal LD50 5000 mg/kg (rabbit) (OECD 402)

Inhalative LC50/4 h >140->2000 mg/l (rat) (OCED 403)
 Maximum attainable concentration, mortality does not appear.
 10000 mg/l (zebra fish) (OECD 203)

7439-98-7 Molybdenum

Oral LD50 >5000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rat)

Inhalative LC50/4 h 800 mg/l (trout)
 >5.84 mg/l (rat)

Primary irritant effect• **On the skin:**

Irritant to skin and mucous membranes.
 May cause an allergic skin reaction.

• **On the eye:**

Strong irritant with the danger of severe eye injury.
 Causes serious eye irritation.

• **Sensitization:**

Sensitization possible through skin contact.

Additional toxicological information

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant.

(Contd. on page 12)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding

Carcinogenic categories:

- **IARC (International Agency for Research on Cancer):**

- Group 1 - Carcinogenic to humans
- Group 2A - Probably carcinogenic to humans
- Group 2B - Possibly carcinogenic to humans
- Group 3 - Not classifiable as to its carcinogenicity to humans
- Group 4 - Probably not carcinogenic to humans

13463-67-7	Titanium Dioxide	2B
1317-95-9	Silica	1
7440-02-0	Nickel	1
7631-86-9	Silicon Dioxide	3

- **NTP (National Toxicology Program):**

1317-95-9	Silica	K
7440-02-0	Nickel	R

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

Ecological Information

Toxicity:

- **Aquatic toxicity:**

- 13463-67-7 Titanium Dioxide**
EC50 >1000 mg/l (Water flea)
- 7440-02-0 Nickel**
EC50 1.0 mg/l (Water flea)
- 7631-86-9 Silicon Dioxide**
EC50 >1000 mg/l (daphnia) (OECD 202)
- 7440-50-8 Copper**
EC50 0.04-0.05 mg/l (Water flea)

Persistence and degradability: No further relevant information available.

Behavior in environmental systems:

- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.

Additional ecological information:

- **General notes:**

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment:

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

Other adverse effects: No further relevant information available.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding**13 Disposal considerations****Waste treatment methods:****· Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

Uncleaned packagings:

- Recommendation:** Disposal must be made according to official regulations.

14 Transport information**UN-Number:**

- DOT, ADR, ADN, IMDG, IATA** Non-Regulated Material

UN proper shipping name:

- DOT, ADR, ADN, IMDG, IATA** Non-Regulated Material

Transport hazard class(es):

- DOT, ADR, ADN, IMDG, IATA** Non-Regulated Material

Packing group:

- DOT, ADR, IMDG, IATA** Non-Regulated Material

Environmental hazards:

Not applicable.

Special precautions for user:

Not applicable.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable.

UN "Model Regulation":

Non-Regulated Material

15 Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture:
SARA (Superfund Amendments and Reauthorization):****· Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

7440-39-3 Barium

7429-90-5 Aluminium

7440-02-0 Nickel

7440-50-8 Copper

7440-62-2 Vanadium

1344-28-1 Aluminium Oxide

· TSCA (Toxic Substances Control Act):

7439-89-6 Iron

13463-67-7 Titanium Dioxide

7440-39-3 Barium

7439-93-2 Lithium

1317-61-9 Iron Oxide

7429-90-5 Aluminium

(Contd. on page 14)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding

7440-21-3 Silicon
 7440-02-0 Nickel
 7439-95-4 Magnesium
 7631-86-9 Silicon Dioxide
 1344-28-1 Aluminium Oxide
 1309-48-4 Magnesium Oxide
 7440-50-8 Copper
 7439-98-7 Molybdenum
 7440-44-0 Carbon

California Proposition 65:· **Chemicals known to cause cancer:**

13463-67-7 Titanium Dioxide
 7440-02-0 Nickel

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

Carcinogenic categories:· **EPA (Environmental Protection Agency):**

7440-39-3 Barium
 7440-50-8 Copper

D, CBD(inh), NL(oral)
 D

· **TLV (Threshold Limit Value established by ACGIH):**

13463-67-7 Titanium Dioxide
 7440-39-3 Barium
 1317-95-9 Silica
 7429-90-5 Aluminium
 7440-02-0 Nickel
 1344-28-1 Aluminium Oxide
 1309-48-4 Magnesium Oxide
 7439-98-7 Molybdenum
 7440-67-7 Zirconium

A4
 A4
 A2
 A4
 A5
 A4
 A4
 A3
 A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

13463-67-7 Titanium Dioxide
 1317-95-9 Silica
 7440-02-0 Nickel

(Contd. on page 15)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015


Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



- **Signal word:** Danger

- **Hazard-determining components of labeling:**

Iron
Lithium
Silica
Nickel
Titanium Dioxide

- **Hazard statements:**

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause cancer.
Causes damage to organs through prolonged or repeated exposure.

- **Precautionary statements:**

Do not handle until all safety precautions have been read and understood.
Obtain special instructions before use.
Do not eat, drink or smoke when using this product.
Do not breathe dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Wear respiratory protection.
Wear protective gloves/protective clothing/eye protection/face protection.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Take off contaminated clothing and wash it before reuse.
If in eyes: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
If on skin: Wash with plenty of water.
If skin irritation or rash occurs: Get medical advice/attention.
If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a poison center/doctor if you feel unwell.
If exposed or concerned: Get medical advice/attention.
If experiencing respiratory symptoms: Call a poison center/doctor.
Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding**State Right to Know:**

CAS: 7439-89-6 RTECS: NO 4565500	Iron ◊Flam. Sol. 2, H228; ◊Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320; Combustible Dust	85-99%
CAS: 13463-67-7	Titanium Dioxide ◊Carc. 2, H351; ◊Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H33	0-10%
CAS: 7440-39-3 RTECS: CQ 8370000	Barium ◊Water-react. 2, H261	0-10%
CAS: 1317-95-9	Silica ◊Carc. 1A, H350; ◊STOT SE 3, H335	0-3%
CAS: 7439-93-2 RTECS: OJ 5540000	Lithium ◊Water-react. 1, H260; ◊Skin Corr. 1B, H314	0-9%
CAS: 1317-61-9	Iron Oxide	0-12%
All ingredients are listed.		

Information about limitation of use

- Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

Other Information

SOWESCO urges each end user and recipient of this SDS to study it carefully. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from potential hazards associated with the handling or use of this product. This information is believed to be accurate as of the revision date shown above. However, no warranty, expressed or implied, is given. Because the conditions or methods of use are beyond SOWESCO's control, we assume no liability resulting from the use of this product. Regulatory requirements are subject to change and may differ between various locations. Compliance with all applicable Federal, State, Provincial, and Local laws and regulations remain the responsibility of the user.

- Date of preparation - last revision:** 08/04/2015 - 09/04/2015

Abbreviations and acronyms:

ACGIH: American Conference of Governmental Industrial Hygienists
 Acute Tox. 4: Acute toxicity, Hazard Category 4
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
 Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4
 Carc. 1A: Carcinogenicity, Hazard Category 1A
 Carc. 2: Carcinogenicity, Hazard Category 2
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DOT: US Department of Transportation
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
 Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B
 Flam. Sol. 1: Flammable solids, Hazard Category 1
 Flam. Sol. 2: Flammable solids, Hazard Category 2
 HMIS: Hazardous Materials Identification System (USA)
 IATA: International Air Transport Association
 IMDG: International Maritime Code for Dangerous Goods
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NFPA: National Fire Protection Association (USA)
 PBT: Persistent, Bioaccumulative and Toxic
 Pyr. Sol. 1: Pyrophoric Solids, Hazard Category 1
 Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 Skin Sens. 1: Sensitization - Skin, Hazard Category 1

(Contd. on page 17)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/04/2015

Reviewed on 09/04/2015

Trade name: Carbon Steel Electrodes and Rods for Gas Shielded Arc Welding

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

vPvB: very Persistent and very Bioaccumulative

Water-react. 1: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 1

Water-react. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2

****All data compared to the previous MSDS version has been altered.***

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106