


12/4/2018

		
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172013
NAPA® PREMIUM CONVENTIONAL SAE 5W-30 MOTOR OIL		Version: 1.1
NP75050		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name

: NAPA® PREMIUM CONVENTIONAL SAE 5W-30 MOTOR OIL

*Napa Premium Performance
High Quality Protection
Synthetic Blend SAE 5W-30
#75050*

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet	Emergency telephone number 1-800-VALVOLINE
Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America	Regulatory Information Number 1-800-TEAMVAL
SDS@valvoline.com	Product Information 1-800-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
HEAVY PARAFFINIC DISTILLATE	64742-54-7	Asp. Tox. 1; H304	36.00

**SAFETY DATA SHEET**

Revision Date: 07/31/2016

Print Date: 9/27/2016

SDS Number: R0172013

Version: 1.1

NAPA® PREMIUM CONVENTIONAL SAE 5W-30
MOTOR OIL

NP75050

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	6.88
Benzenesulfonic acid, C10-60- alkyl derivs., sodium salts	90194-32-4	Eye Irrit. 2A; H319	6.21
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	1.88

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through

**SAFETY DATA SHEET**

Revision Date: 07/31/2016

Print Date: 9/27/2016

SDS Number: R0172013

Version: 1.1

NAPA® PREMIUM CONVENTIONAL SAE 5W-30
MOTOR OIL

NP75050

breathing, swallowing, and/or passage of the material through the skin may include:

acne

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO₂)

Dry chemical

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.



SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 9/27/2016

SDS Number: R0172013

Version: 1.1

NAPA® PREMIUM CONVENTIONAL SAE 5W-30
MOTOR OIL

NP75050

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRANS
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	PEL	500 ppm 2,000 mg/m3	OSHA_TRANS
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRANS
		TWA	5 mg/m3 Mist.	Z1A
		TWA	400 ppm 1,600 mg/m3	Z1A

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

**SAFETY DATA SHEET**

Revision Date: 07/31/2016

Print Date: 9/27/2016

SDS Number: R0172013

Version: 1.1

NAPA® PREMIUM CONVENTIONAL SAE 5W-30
MOTOR OIL

NP75050

required.

- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
Safety shoes
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 390 °F / > 199 °C
Method: Cleveland open cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : 6 %(V)
Calculated Explosive Limit
- Lower explosion limit : 1 %(V)
Calculated Explosive Limit
- Vapour pressure : 1.3333333 hPa (20 °C)
Calculated Vapor Pressure
- Relative vapour density : No data available
- Relative density : 0.876 (15.6 °C)
- Density : 0.8599 g/cm³ (15.6 °C)

Solubility(ies)

**SAFETY DATA SHEET**

Revision Date: 07/31/2016

Print Date: 9/27/2016

SDS Number: R0172013

Version: 1.1

NAPA® PREMIUM CONVENTIONAL SAE 5W-30
MOTOR OIL

NP75050

Acute oral toxicity : LD 50 (Rat): > 15 g/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Not irritating to skin

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Mildly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Not irritating to eyes

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to eyes

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Irritating to eyes

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Mildly irritating to eyes


Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

		Page: 8
		Revision Date: 07/31/2016
SAFETY DATA SHEET		Print Date: 9/27/2016
		SDS Number: R0172013
NAPA® PREMIUM CONVENTIONAL SAE 5W-30 MOTOR OIL NP75050		Version: 1.1

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

HEAVY PARAFFINIC DISTILLATE:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10.000 mg/l



SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 9/27/2016

SDS Number: R0172013

Version: 1.1

NAPA® PREMIUM CONVENTIONAL SAE 5W-30
MOTOR OIL

NP75050

aquatic invertebrates

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Persistence and degradability

Components:

No data available

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**SAFETY DATA SHEET**

Revision Date: 07/31/2016

Print Date: 9/27/2016

SDS Number: R0172013

Version: 1.1

NAPA® PREMIUM CONVENTIONAL SAE 5W-30
MOTOR OIL

NP75050

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG


Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant

no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

		Page: 11
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172013
NAPA® PREMIUM CONVENTIONAL SAE 5W-30 MOTOR OIL		Version: 1.1
NP75050		

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : No SARA Hazards

SARA 313 Component(s) : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	50.00 - 70.00 %
HEAVY PARAFFINIC DISTILLATE	64742-54-7	30.00 - 50.00 %
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	5.00 - 10.00 %
Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts	90194-32-4	5.00 - 10.00 %
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	1.00 - 5.00 %


New Jersey Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	50.00 - 70.00 %
HEAVY PARAFFINIC DISTILLATE	64742-54-7	30.00 - 50.00 %
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	5.00 - 10.00 %
Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts	90194-32-4	5.00 - 10.00 %
POLYOLEFIN AMIDE ALKENEAMINE	Not Assigned	1.00 - 5.00 %
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	1.00 - 5.00 %

California Prop 65 Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL.
AUSTR	: On the inventory, or in compliance with the inventory
KECL	: On the inventory, or in compliance with the inventory

		Page: 12
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172013
NAPA® PREMIUM CONVENTIONAL SAE 5W-30 MOTOR OIL		Version: 1.1
NP75050		

PICCS : On the inventory, or in compliance with the inventory

IECSC : q (quantity restricted)


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016

NFPA:	HMIS III:						
<p>Flammability</p>  <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td>HEALTH</td> <td>1</td> </tr> <tr> <td>FLAMMABILITY</td> <td>1</td> </tr> <tr> <td>PHYSICAL HAZARD</td> <td>0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	1	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	1						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.


- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1 800 825 8651)

		Page: 13
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172013
NAPA® PREMIUM CONVENTIONAL SAE 5W-30 MOTOR OIL		Version: 1.1
NP75050		

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System