9/5/24

# SAFETY DATA SHEET ZEP FOAMING WALL CLEANER

Version 5.1

Revision Date 10/01/2023 ·

Print Date 07/03/2024

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name

ZEP FOAMING WALL CLEANER

Material number

ZUFWC18

Manufacturer or supplier's details

Company

Zep Inc.

Address

350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone

Compliance Services - 877-428-9937

Emergency telephone numbers		
For SDS Information	:	Compliance Services - 877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

# **SECTION 2. HAZARDS IDENTIFICATION**

# **Emergency Overview**

Appearance	Aerosol containing a liquefied gas	
Colour	off-white, opaque	
Odour	ammoniacal	

**GHS Classification** 

Gases under pressure

: Liquefied gas

GHS label elements

Hazard pictograms

Gas cy linder

Signal word

: Warning

Hazard statements

: H280 Contains gas under pressure; may explode if heated.

Precautionary statements

: Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P251 Pressurized container: Do not pierce or burn, even after

use.

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place.

P412 Do not expose to temperatures exceeding 50 °C/ 122 °F.

Version 5.1

Revision Date 10/01/2023

Print Date 07/03/2024

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration [%]
butane	106-97-8	>= 1 - < 5
2-(2-butoxyethoxy)ethanol	112-34-5	>= 1 - < 5
1-butoxypropan-2-ol	5131-66-8	>= 1 - < 5
propane	74-98-6	>= 1 - < 5
sodium nitrite	7632-00-0	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice

Do not leave the victim unattended.

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

If inhaled

: If unconscious, place in recovery position, and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact

: Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist. Immediately flush eye(s) with plenty of water.

If swallowed

Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed

Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation.

Notes to physician

: Treat symptomatically. Symptoms may be delayed.

Version 5.1

Revision Date 10/01/2023

Print Date 07/03/2024

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media

: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet

Unsuitable extinguishing

media

High volume water jet

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

# SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protective equipment. Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

# SECTION 7. HANDLING AND STORAGE

Advice on safe handling

: Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Dispose of rinse water in accordance with local and national

Version 5.1

Revision Date 10/01/2023

Print Date 07/03/2024

regulations.

Always replace cap after use.

Do not breathe vapours or spray mist.

Conditions for safe storage

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Keep in a dry, cool and well-ventilated place.

Materials to avoid

: Do not store near acids.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL

Engineering measures

: effective ventilation in all processing areas

#### Personal protective equipment

Respiratory protection

: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks

: The suitability for a specific workplace should be discussed

Version 5.1

Revision Date 10/01/2023

Print Date 07/03/2024

with the producers of the protective gloves.

Access to clean water to rinse eyes must be available, options Eye protection

include: eye wash stations or showers, or eye wash bottles

with pure water.

Tightly fitting safety goggles

Skin and body protection Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Wash hands before breaks and at the end of workday. Hygiene measures

When using do not eat, drink or smoke.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

: Aerosol containing a liquefied gas Appearance

Colour off-white, opaque

Odour ammoniacal

Odour Threshold No data available

10 - 11 pН

: No data available Melting point/freezing point

101.67 °C Boiling point

Flash point

Not applicable

Evaporation rate n-Butyl Acetate = 1.0

The product is not flammable.

Flammability (solid, gas, liquid)

Density

Upper explosion limit : Not applicable Lower explosion limit Not applicable

Vapour pressure : Not applicable Relative vapour density No data available

Solubility(ies)

Water solubility : soluble in hot water, soluble in cold water

: No data available

Solubility in other solvents not determined

Partition coefficient: n-

: No data available

octanol/water

Auto-ignition temperature : not determined

: No data available Thermal decomposition

Viscosity

Version 5.1

Revision Date 10/01/2023

Print Date 07/03/2024

Viscosity, kinematic

: No data available

Heat of combustion

: 4.30 kJ/g

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity

: Stable

Chemical stability

: Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

: Heat, flames and sparks.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

: Acids

Hazardous decomposition

products

: Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure

: Effects may be delayed, symptoms may include minor eye or

skin irritation.

Overexposure may cause mild eye or skin irritation. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

**IARC** 

Group 2A: Probably carcinogenic to humans

sodium nitrite

7632-00-0

ACGIH

No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

**OSHA** 

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

**Product:** 

Version 5.1

Revision Date 10/01/2023

Print Date 07/03/2024

Acute oral toxicity

: Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

# Skin corrosion/irritation

#### **Product:**

Remarks: May cause skin irritation and/or dermatitis.

# Serious eye damage/eye irritation

#### **Product:**

Remarks: May irritate eyes.

# Respiratory or skin sensitisation

No data available

# Germ cell mutagenicity

No data available

# Carcinogenicity

No data available

# Reproductive toxicity

No data available

#### STOT - single exposure

No data available

# STOT - repeated exposure

No data available

# Aspiration toxicity

No data available

# **Further information**

# **Product:**

Remarks: No data available

#### SECTION 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

No data available

# Persistence and degradability

No data available

Bioaccumulative potential

# SAFETY DATA SHEET

# ZEP FOAMING WALL CLEANER

Version 5.1

Revision Date 10/01/2023

Print Date 07/03/2024

**Product:** 

Partition coefficient: n-

: Remarks: No data available

octanol/water Components:

butane : Partition coefficient: n-

: Pow: 2.89

octanol/water

2-(2-butoxyethoxy)ethanol:

Partition coefficient: n-

: Pow: 1

octanol/water

1-butoxypropan-2-ol:

Partition coefficient: n-

: Pow: 1.2

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Regulation

40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

# **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues

Dispose of in accordance with local regulations.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging

Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Version 5.1 Revision Date 10/01/2023 Print Date 07/03/2024

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

TSCA list : No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export

notification requirements:

sodium nitrite 7632-00-0

#### EPCRA - Emergency Planning and Community Right-to-Know Act

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium nitrite	7632-00-0	100	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Gases under pressure

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

2-(2-butoxyethoxy)ethanol 112-34-5 2.3748 %

California Prop. 65

This product does not contain any chemicals known to State of

Version 5.1

Revision Date 10/01/2023

Print Date 07/03/2024

California to cause cancer, birth defects, or any other reproductive harm.

# The components of this product are reported in the following inventories:

DSL

All components of this product are on the Canadian DSL

TSCA

On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

# Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

**SECTION 16. OTHER INFORMATION** 

Version 5.1

Revision Date 10/01/2023

Print Date 07/03/2024

#### **Further information**

#### NFPA:

HEALTH	1
FLAMMABILITY	2
INSTABILITY	0
SPECIAL HAZARD.	

<sup>0 =</sup> not significant, 1 = Slight,

# HMIS III:

HEALTH	1
FLAMMABILITY	2
PHYSICAL HAZARD	2

<sup>0 =</sup> not significant, 1 = Slight,

#### **OSHA - GHS Label Information:**

Hazard pictograms



Signal word Hazard statements Precautionary statements Warning:

Contains gas under pressure; may explode if heated.

**Prevention:** Keep aw ay from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use.

Storage: Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. **Dis pos al:** Dispose of contents/container in accordance with local regulation.

Version:	5.1
Revision Date:	10/01/2023
Print Date:	07/03/2024

<sup>2 =</sup> Moderate, 3 = High

<sup>4 =</sup> Extreme

<sup>2 =</sup> Moderate, 3 = High

<sup>4 =</sup> Extreme, \* = Chronic

Version 5.1

Revision Date 10/01/2023

Print Date 07/03/2024

9

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.