



Close this window

7/19/2018

SDS

Starting Fluid with Upper
Cylinder Lubricant By Pyroil
PYSFR11

Common Name: PYROIL REGULAR STARTING FLUID

Manufacturer: ASHLAND CHEMICAL

SDS Revision Date: 1/14/2010

SDS Format: No Format Specified

Item Number(s): 21A070, 21A071

Manufacturer Model Number(s):

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

- [1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE](#)
- [2. HAZARDS IDENTIFICATION](#)
- [3. COMPOSITION/INFORMATION ON INGREDIENTS](#)
- [4. FIRST AID MEASURES](#)
- [5. FIRE-FIGHTING MEASURES](#)
- [6. ACCIDENTAL RELEASE MEASURES](#)
- [7. HANDLING AND STORAGE](#)
- [8. EXPOSURE CONTROLS/PERSONAL PROTECTION](#)
- [9. PHYSICAL AND CHEMICAL PROPERTIES](#)
- [10. STABILITY AND REACTIVITY](#)
- [11. TOXICOLOGICAL INFORMATION](#)
- [12. ECOLOGICAL INFORMATION](#)
- [13. DISPOSAL CONSIDERATIONS](#)
- [14. TRANSPORT INFORMATION](#)
- [15. REGULATORY INFORMATION](#)
- [16. OTHER INFORMATION](#)

SAFETY DATA SHEET

ASHLAND (R*)

PYROIL (R*) REGULAR STARTING FLUID PYSFR11

REVISION DATE: 01/14/2010

PRINT DATE: 1/21/2010

MSDS NUMBER: R0340954

VERSION: 4.0

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE

COMPANY/UNDERTAKING

ASHLAND
P.O. BOX 2219
COLUMBUS, OH 43216

REGULATORY INFORMATION NUMBER: 1-800-325-3751

TELEPHONE: 614-790-3333

EMERGENCY TELEPHONE: 1-800-ASHLAND (1-800-274-5263)

PRODUCT NAME: PYROIL(R*) REGULAR STARTING FLUID

PRODUCT CODE: PYSFR11

PRODUCT USE DESCRIPTION: NO DATA

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

APPEARANCE: AEROSOL

WARNING!

EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. CAUSES EYE IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

POTENTIAL HEALTH EFFECTS:

EXPOSURE ROUTES: INHALATION, SKIN ABSORPTION, SKIN CONTACT, EYE CONTACT

EYE CONTACT:
CAN CAUSE SEVERE EYE IRRITATION. SYMPTOMS INCLUDE STINGING, TEARING,
REDDNESS, AND SWELLING OF EYES. CAN INJURE EYE TISSUE.

SKIN CONTACT:
MAY CAUSE MILD SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY THE
SKIN. SYMPTOMS MAY INCLUDE REDNESS, BURNING, DRYING AND CRACKING OF SKIN,
AND SKIN BURNS. PASSAGE OF THIS MATERIAL INTO THE BODY THROUGH THE SKIN IS
POSSIBLE, BUT IT IS UNLIKELY THAT THIS WOULD RESULT IN HARMFUL EFFECTS
DURING SAFE HANDLING AND USE.

INGESTION:
SWALLOWING SMALL AMOUNTS OF THIS MATERIAL DURING NORMAL HANDLING IS NOT
LIKELY TO CAUSE HARMFUL EFFECTS. SWALLOWING LARGE AMOUNTS MAY BE HARMFUL.
THIS MATERIAL CAN GET INTO THE LUNGS DURING SWALLOWING OR VOMITING. THIS
RESULTS IN LUNG INFLAMMATION AND OTHER LUNG INJURY.

INHALATION:
BREATHING AEROSOL AND/OR MIST IS POSSIBLE WHEN MATERIAL IS SPRAYED.
AEROSOL AND MIST MAY PRESENT A GREATER RISK OF INJURY BECAUSE MORE MATERIAL
MAY BE PRESENT IN THE AIR THAN FROM VAPOR ALONE.

BREATHING SMALL AMOUNTS OF THIS MATERIAL DURING NORMAL HANDLING IS NOT
LIKELY TO CAUSE HARMFUL EFFECTS.

BREATHING LARGE AMOUNTS MAY BE HARMFUL. SYMPTOMS ARE NOT EXPECTED AT AIR
CONCENTRATIONS BELOW THE RECOMMENDED EXPOSURE LIMITS, IF APPLICABLE (SEE
SECTION 8.).

AGGRAVATED MEDICAL CONDITION:

PREEXISTING DISORDERS OF THE FOLLOWING ORGANS (OR ORGAN SYSTEMS) MAY BE
AGGRAVATED BY EXPOSURE TO THIS MATERIAL:
SKIN, LUNG (FOR EXAMPLE, ASTHMA-LIKE CONDITIONS)

SYMPTOMS:

SIGNS AND SYMPTOMS OF EXPOSURE TO THIS MATERIAL THROUGH BREATHING,
SWALLOWING, AND/OR PASSAGE OF THE MATERIAL THROUGH THE SKIN MAY INCLUDE:
STOMACH OR INTESTINAL UPSET (NAUSEA, VOMITING, DIARRHEA), IRRITATION (NOSE,
THROAT, AIRWAYS), CENTRAL NERVOUS SYSTEM DEPRESSION (DIZZINESS, DROWSINESS,
WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS), HIGH BLOOD PRESSURE,
EFFECTS ON HEART RATE, EFFECTS ON BREATHING RATE

TARGET ORGANS:
EXPOSURE TO THIS MATERIAL (OR A COMPONENT) HAS BEEN FOUND TO CAUSE KIDNEY
DAMAGE IN MALE RATS.

THE MECHANISM BY WHICH THIS TOXICITY OCCURS IS SPECIFIC TO THE MALE RAT AND THE KIDNEY EFFECTS ARE NOT EXPECTED TO OCCUR IN HUMANS.

CARCINOGENICITY:

THIS MATERIAL IS NOT LISTED AS A CARCINOGEN BY THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC), THE NATIONAL TOXICOLOGY PROGRAM (NTP), OR THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA).

REPRODUCTIVE HAZARD:

THERE ARE NO DATA AVAILABLE FOR ASSESSING RISK TO THE FETUS FROM MATERNAL EXPOSURE TO THIS MATERIAL.

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS	CAS-NO.	CONCENTRATION
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	>/= 70-<80%
ETHYL ETHER	60-29-7	>/= 15-<20%
CARBON DIOXIDE	124-38-9	>/= 1.5-<5%

4. FIRST AID MEASURES

EYES:

IF SYMPTOMS DEVELOP, IMMEDIATELY MOVE INDIVIDUAL AWAY FROM EXPOSURE AND INTO FRESH AIR.

FLUSH EYES GENTLY WITH WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS APART; SEEK IMMEDIATE MEDICAL ATTENTION.

SKIN:

REMOVE CONTAMINATED CLOTHING. FLUSH EXPOSED AREA WITH LARGE AMOUNTS OF WATER. IF SKIN IS DAMAGED, SEEK IMMEDIATE MEDICAL ATTENTION. IF SKIN IS NOT DAMAGED AND SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION. LAUNDRER CLOTHING BEFORE REUSE.

INGESTION:

SEEK MEDICAL ATTENTION. IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS, DO NOT GIVE ANYTHING BY MOUTH; PLACE INDIVIDUAL ON THE LEFT SIDE WITH THE HEAD DOWN. CONTACT A PHYSICIAN, MEDICAL FACILITY, OR POISON CONTROL CENTER FOR ADVICE ABOUT WHETHER TO INDUCE VOMITING. IF POSSIBLE, DO NOT LEAVE INDIVIDUAL UNATTENDED.

INHALATION:
IF SYMPTOMS DEVELOP, MOVE INDIVIDUAL AWAY FROM EXPOSURE AND INTO FRESH AIR. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. KEEP PERSON WARM AND QUIET; SEEK IMMEDIATE MEDICAL ATTENTION.

NOTES TO PHYSICIAN:

HAZARDS:
INHALATION OF HIGH CONCENTRATIONS OF THIS MATERIAL, AS COULD OCCUR IN ENCLOSED SPACES OR DURING DELIBERATE ABUSE, MAY BE ASSOCIATED WITH CARDIAC ARRHYTHMIAS. SYMPATHOMIMETIC DRUGS MAY INITIATE CARDIAC ARRHYTHMIAS IN PERSONS EXPOSED TO THIS MATERIAL.

TREATMENT: NO INFORMATION AVAILABLE.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: WATER MIST, CARBON DIOXIDE (CO₂), DRY CHEMICAL

HAZARDOUS COMBUSTION PRODUCTS:
ALDEHYDES, CARBON DIOXIDE AND CARBON MONOXIDE, ORGANIC COMPOUNDS, HYDROCARBONS

PRECAUTIONS FOR FIRE-FIGHTING:
MATERIAL IS VOLATILE AND READILY GIVES OFF VAPORS WHICH MAY TRAVEL ALONG THE GROUND OR BE MOVED BY VENTILATION AND IGNITED BY PILOT LIGHTS, FLAMES, SPARKS, HEATERS, SMOKING, ELECTRIC MOTORS, STATIC DISCHARGE OR OTHER IGNITION SOURCES AT LOCATIONS NEAR THE MATERIAL HANDLING POINT. NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY. WEAR FULL FIREFIGHTING TURN-OUT GEAR (FULL BUNKER GEAR), AND RESPIRATORY PROTECTION (SCBA).

NFPA FLAMMABLE AND COMBUSTIBLE LIQUIDS CLASSIFICATION:
FLAMMABLE LIQUID CLASS 1A

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:
FOR PERSONAL PROTECTION SEE SECTION 8. PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS).



ENVIRONMENTAL PRECAUTIONS:
PREVENT RUN-OFF TO SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED, THAT A SPILL HAS OCCURRED.

METHODS FOR CLEANING UP:
ABSORB LIQUID ON VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL.

7. HANDLING AND STORAGE

HANDLING:
CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED. AVOID PROLONGED OR FREQUENTLY REPEATED SKIN CONTACT WITH THIS MATERIAL. SKIN CONTACT CAN BE MINIMIZED BY WEARING IMPERVIOUS PROTECTIVE GLOVES. AS WITH ALL PRODUCTS OF THIS NATURE, GOOD PERSONAL HYGIENE IS ESSENTIAL. HANDS AND OTHER EXPOSED AREAS SHOULD BE WASHED THOROUGHLY WITH SOAP AND WATER AFTER CONTACT, ESPECIALLY BEFORE EATING AND/OR SMOKING. REGULAR LAUNDERING OF CONTAMINATED CLOTHING IS ESSENTIAL TO REDUCE INDIRECT SKIN CONTACT WITH THIS MATERIAL. STATIC IGNITION HAZARD CAN RESULT FROM HANDLING AND USE. ELECTRICALLY BOND AND GROUND ALL CONTAINERS, PERSONNEL AND EQUIPMENT BEFORE TRANSFER OR USE OF MATERIAL. SPECIAL PRECAUTIONS MAY BE NECESSARY TO DISSIPATE STATIC ELECTRICITY FOR NON-CONDUCTIVE CONTAINERS. USE PROPER BONDING AND GROUNDING DURING PRODUCT TRANSFER AS DESCRIBED IN NATIONAL FIRE PROTECTION ASSOCIATION DOCUMENT NFPA 77. HYDROCARBON SOLVENTS ARE BASICALLY NON-CONDUCTORS OF ELECTRICITY AND CAN BECOME ELECTROSTATICALLY CHARGED DURING MIXING, FILTERING OR PUMPING AT HIGH FLOW RATES. IF THIS CHARGE REACHES A SUFFICIENTLY HIGH LEVEL, SPARKS CAN FORM THAT MAY IGNITE THE VAPORS OF FLAMMABLE LIQUIDS.

STORAGE: DO NOT STORE NEAR EXTREME HEAT, OPEN FLAME, OR SOURCES OF IGNITION.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC

64742-89-8

OSHA Z1	TIME WEIGHTED AVERAGE	500 PPM
ACGIH	TIME WEIGHTED AVERAGE	300 PPM
ACGIH	TIME WEIGHTED AVERAGE	1,370 MG/M3

ETHYL ETHER

TIME WEIGHTED AVERAGE 400 PPM
 SHORT TERM EXPOSURE LIMIT 500 PPM
 PERMISSIBLE EXPOSURE LIMIT 400 PPM
 PERMISSIBLE EXPOSURE LIMIT 1,200 MG/M3

124-38-9

CARBON DIOXIDE

TIME WEIGHTED AVERAGE 5,000 PPM
 SHORT TERM EXPOSURE LIMIT 30,000 PPM
 RECOMMENDED EXPOSURE LIMIT 5,000 PPM
 (REL)
 RECOMMENDED EXPOSURE LIMIT 9,000 MG/M3
 (REL)
 SHORT TERM EXPOSURE LIMIT 30,000 PPM
 SHORT TERM EXPOSURE LIMIT 54,000 MG/M3
 PERMISSIBLE EXPOSURE LIMIT 5,000 PPM
 PERMISSIBLE EXPOSURE LIMIT 9,000 MG/M3

GENERAL ADVICE:
 THESE RECOMMENDATIONS PROVIDE GENERAL GUIDANCE FOR HANDLING THIS PRODUCT.
 PERSONAL PROTECTIVE EQUIPMENT SHOULD BE SELECTED FOR INDIVIDUAL APPLICATIONS
 AND SHOULD CONSIDER FACTORS WHICH AFFECT EXPOSURE POTENTIAL, SUCH AS
 HANDLING PRACTICES, CHEMICAL CONCENTRATIONS AND VENTILATION. IT IS
 ULTIMATELY THE RESPONSIBILITY OF THE EMPLOYER TO FOLLOW REGULATORY
 GUIDELINES ESTABLISHED BY LOCAL AUTHORITIES.

EXPOSURE CONTROLS:
 PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO
 MAINTAIN EXPOSURE BELOW EXPOSURE GUIDELINES (IF APPLICABLE) OR BELOW LEVELS
 THAT CAUSE KNOWN, SUSPECTED OR APPARENT ADVERSE EFFECTS.

EYE PROTECTION:
 WEAR CHEMICAL SPLASH GOGGLES WHEN THERE IS THE POTENTIAL FOR EXPOSURE OF THE
 EYES TO LIQUID, VAPOR OR MIST.

SKIN AND BODY PROTECTION:

WEAR RESISTANT GLOVES (CONSULT YOUR SAFETY EQUIPMENT SUPPLIER).

WEAR NORMAL WORK CLOTHING INCLUDING LONG PANTS, LONG-SLEEVED SHIRTS AND FOOT COVERING TO PREVENT DIRECT CONTACT OF THE PRODUCT WITH THE SKIN. LAUNDRER CLOTHING BEFORE REUSE. IF SKIN IRRITATION DEVELOPS, CONTACT YOUR FACILITY HEALTH AND SAFETY PROFESSIONAL OR YOUR LOCAL SAFETY EQUIPMENT SUPPLIER TO DETERMINE THE PROPER PERSONAL PROTECTIVE EQUIPMENT FOR YOUR USE.

RESPIRATORY PROTECTION:

A NIOSH-APPROVED AIR-PURIFYING RESPIRATOR WITH AN APPROPRIATE CARTRIDGE AND/OR FILTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS (IF APPLICABLE) OR IF OVEREXPOSURE HAS OTHERWISE BEEN DETERMINED. PROTECTION PROVIDED BY AIR-PURIFYING RESPIRATORS IS LIMITED. USE A POSITIVE PRESSURE, AIR-SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN OR ANY OTHER CIRCUMSTANCES WHERE AN AIR-PURIFYING RESPIRATOR MAY NOT PROVIDE ADEQUATE PROTECTION.



9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: AEROSOL

FORM: AEROSOL

COLOR: NO DATA

ODOR: NO DATA

BOILING POINT/BOILING RANGE:
34.60 DEG. C @ 1,013.23 HPA CALCULATED PHASE TRANSITION LIQUID/GAS

pH: NO DATA

FLASH POINT: -45.00 DEG. C CALCULATED FLASH POINT

EVAPORATION RATE: NO DATA

LOWER EXPLOSION LIMIT/UPPER EXPLOSION LIMIT: 1.05 % (V) / 36.5 % (V)

VAPOR PRESSURE: 717.261 HPA @ 25 DEG. C CALCULATED VAPOR PRESSURE

VAPOR DENSITY: NO DATA

DENSITY: 0.7114 G/CM3 @ 60.01 DEG. F / 15.56 DEG. C

SOLUBILITY: NO DATA

PARTITION COEFFICIENT:
n-OCTANOL/WATER: NO DATA

LOG POW: NO DATA AVAILABLE

AUTOIGNITION TEMPERATURE: NO DATA

10. STABILITY AND REACTIVITY

STABILITY: STABLE.

CONDITIONS TO AVOID: HEAT, FLAMES AND SPARKS.

INCOMPATIBLE PRODUCTS: HALOGENS, STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS:

ALDEHYDES, CARBON DIOXIDE AND CARBON MONOXIDE, ORGANIC COMPOUNDS,
HYDROCARBONS

HAZARDOUS REACTIONS: PRODUCT WILL NOT UNDERGO HAZARDOUS POLYMERIZATION.

THERMAL DECOMPOSITION: NO DATA

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL TOXICITY:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:
LD50 RAT: >8,000 MG/KG

ETHYL ETHER:
LD50 RAT: 3,230 - 3,920 MG/KG

CARBON DIOXIDE: NO DATA AVAILABLE

ACUTE INHALATION TOXICITY:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:
LC50 RAT: 3400 PPM, 4 H

ETHYL ETHER:
LC50 RAT: 32,000 MG/L, 4 H



CARBON DIOXIDE: NO DATA AVAILABLE

ACUTE DERMAL TOXICITY:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

LD50 RAT: >4,000 MG/KG

ETHYL ETHER: NO DATA AVAILABLE

CARBON DIOXIDE: NO DATA AVAILABLE

12. ECOLOGICAL INFORMATION

BIODEGRADABILITY:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC: NO DATA AVAILABLE

ETHYL ETHER: NO DATA AVAILABLE

CARBON DIOXIDE: NO DATA AVAILABLE

BIOACCUMULATION:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC: NO DATA AVAILABLE

ETHYL ETHER: NO DATA AVAILABLE

CARBON DIOXIDE: NO DATA AVAILABLE

ECOTOXICITY EFFECTS:

TOXICITY TO FISH:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC: NO DATA AVAILABLE

ETHYL ETHER: NO DATA AVAILABLE

CARBON DIOXIDE: NO DATA AVAILABLE

TOXICITY TO DAPHNIA AND OTHER AQUATIC INVERTEBRATES.:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC: NO DATA AVAILABLE

ETHYL ETHER: NO DATA AVAILABLE

CARBON DIOXIDE: NO DATA AVAILABLE

TOXICITY TO ALGAE:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC: NO DATA AVAILABLE

ETHYL ETHER: NO DATA AVAILABLE

CARBON DIOXIDE: NO DATA AVAILABLE

TOXICITY TO BACTERIA:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC: NO DATA AVAILABLE

ETHYL ETHER: NO DATA AVAILABLE

CARBON DIOXIDE: NO DATA AVAILABLE

BIOCHEMICAL OXYGEN DEMAND (BOD):

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC: NO DATA AVAILABLE
ETHYL ETHER: NO DATA AVAILABLE
CARBON DIOXIDE: NO DATA AVAILABLE

CHEMICAL OXYGEN DEMAND (COD):
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC: NO DATA AVAILABLE
ETHYL ETHER: NO DATA AVAILABLE
CARBON DIOXIDE: NO DATA AVAILABLE

ADDITIONAL ECOLOGICAL INFORMATION:
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC: NO DATA AVAILABLE
ETHYL ETHER: NO DATA AVAILABLE
CARBON DIOXIDE: NO DATA AVAILABLE

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS:
DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. FOR ASSISTANCE WITH YOUR WASTE MANAGEMENT NEEDS - INCLUDING DISPOSAL, RECYCLING AND WASTE STREAM REDUCTION, CONTACT ASHLAND DISTRIBUTION'S ENVIRONMENTAL SERVICES GROUP AT 800-637-7922.

14. TRANSPORT INFORMATION

REGULATION:

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT
					/ LTD. QTY.

U.S. DOT - ROAD:

ORM-D, CONSUMER COMMODITY

U.S. DOT - RAIL:

ORM-D, CONSUMER COMMODITY

U.S. DOT - INLAND WATERWAYS:

ORM-D, CONSUMER COMMODITY

TRANSPORT CANADA - ROAD:

UN 1950 AEROSOLS 2.1

TRANSPORT CANADA - RAIL:

UN 1950 AEROSOLS 2.1

TRANSPORT CANADA - INLAND WATERWAYS:

UN 1950 AEROSOLS 2.1

INTERNATIONAL MARITIME DANGEROUS GOODS:

UN 1950 AEROSOLS 2.1 LIMITED QUANTITY

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:

UN 1950 AEROSOLS, FLAMMABLE (ENGINE STARTING FLUID) 2.1

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:

UN 1950 AEROSOLS, FLAMMABLE (ENGINE STARTING FLUID) 2.1

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES:

UN 1950 AEROSOLS 2

*ORM = ORM-D

CBL = COMBUSTIBLE LIQUID

DANGEROUS GOODS DESCRIPTIONS (IF INDICATED ABOVE) MAY NOT REFLECT QUANTITY, END-USE OR REGION-SPECIFIC EXCEPTIONS THAT CAN BE APPLIED. CONSULT SHIPPING DOCUMENTS FOR DESCRIPTIONS THAT ARE SPECIFIC TO THE SHIPMENT.

15. REGULATORY INFORMATION

CALIFORNIA PROP. 65:

WARNING!

THIS PRODUCT CONTAINS A CHEMICAL KNOWN IN THE STATE OF CALIFORNIA TO CAUSE CANCER.



BENZENE

WARNING!

THIS PRODUCT CONTAINS A CHEMICAL KNOWN IN THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

BENZENE

TOLUENE

SARA HAZARD CLASSIFICATION:
ACUTE HEALTH HAZARD
FIRE HAZARD
SUDDEN RELEASE OF PRESSURE HAZARD

NEW JERSEY RTK LABEL INFORMATION:

n-HEPTANE 142-82-5

ETHYL ETHER 60-29-7

CARBON DIOXIDE 124-38-9

PENNSYLVANIA RTK LABEL INFORMATION:

n-HEPTANE 142-82-5

ETHYL ETHER 60-29-7

CARBON DIOXIDE 124-38-9

BENZENE 71-43-2

NOTIFICATION STATUS:

EU. EINECS: Y (POSITIVE LISTING)

US. TOXIC SUBSTANCES CONTROL ACT: Y (POSITIVE LISTING)

AUSTRALIA. INDUSTRIAL CHEMICAL (NOTIFICATION AND ASSESSMENT) ACT:
Y (POSITIVE LISTING)

CANADA. CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA). DOMESTIC SUBSTANCES LIST (DSL). (CAN. GAZ. PART II, VOL. 133):
Y (POSITIVE LISTING)

JAPAN. KASHIN-HOU LAW LIST: N (NEGATIVE LISTING)

KOREA. TOXIC CHEMICAL CONTROL LAW (TCCL) LIST: Y (POSITIVE LISTING)

PHILIPPINES. THE TOXIC SUBSTANCES AND HAZARDOUS AND NUCLEAR WASTE CONTROL ACT: Y (POSITIVE LISTING)

CHINA. INVENTORY OF EXISTING CHEMICAL SUBSTANCES: Y (POSITIVE LISTING)

NEW ZEALAND. INVENTORY OF CHEMICALS (NZIOC), AS PUBLISHED BY ERMA NEW ZEALAND: Y (POSITIVE LISTING)

REPORTABLE QUANTITY - PRODUCT:

US. EPA CERCLA HAZARDOUS SUBSTANCES (40 CFR 302): 511 LBS

REPORTABLE QUANTITY-COMPONENTS:

ETHYL ETHER 60-29-7 100 LBS

HMS NFPA

HEALTH	2	1
FLAMMABILITY	4	4
PHYSICAL HAZARDS	0	
INSTABILITY		0
SPECIFIC HAZARD		

16. OTHER INFORMATION

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES. THIS MSDS HAS BEEN PREPARED BY ASHLAND'S ENVIRONMENTAL HEALTH AND SAFETY DEPARTMENT (1-800-325-3751).

