

10/12/2018

# Safety Data Sheet

## Loctite SF7900 Ceramic Shield For Welding



Revision Number: 001.2

Issue date: 10/07/2014


### 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>LOCTITE 7900 CERAMISHIELD known as Loctite SF 7900 Ceramic Shield</b>	<b>IDH number:</b>	1616692
<b>Product type:</b>	Lubricant	<b>Item number:</b>	1616692
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Corporation	Telephone: (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

### 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
<b>WARNING:</b>	CONTENTS UNDER PRESSURE. FLAMMABLE AEROSOL. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL.	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3



#### Precautionary Statements

**Prevention:** Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye and face protection. Wear protective gloves.

**Response:** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Propane/Isobutane	68476-86-8	30 - 60
Acetone	67-64-1	10 - 30
Methyl ethyl ketone	78-93-3	10 - 30
Ethylcellulose	9004-57-3	0.1 - 1

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
<b>Skin contact:</b>	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Get medical attention. Wash clothing before reuse.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Symptoms:</b>	See Section 11.
<b>Notes to physician:</b>	Treat symptomatically and supportively.

### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
<b>Unusual fire or explosion hazards:</b>	DANGEROUS when exposed to heat or flame. This material can be ignited by flame or spark under all normal atmospheric conditions. Vapors are heavier than air and may travel to ignition sources and flash back. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
<b>Hazardous combustion products:</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
-----------------------------------	---

**Clean-up methods:**

Remove all sources of ignition. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

## 7. HANDLING AND STORAGE

**Handling:**

For industrial use only. Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed.

**Storage:**

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. Do not store with oxidizing materials.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Propane/Isobutane	None	None	None	None
Acetone	750 ppm STEL 500 ppm TWA	1,000 ppm (2,400 mg/m3) PEL	None	None
Methyl ethyl ketone	200 ppm TWA 300 ppm STEL	200 ppm (590 mg/m3) PEL	None	None
Ethylcellulose	None	None	None	None

**Engineering controls:**

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

**Respiratory protection:**

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:**

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	White
<b>Odor:</b>	Solvent
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	6 - 8
<b>Vapor pressure:</b>	231 mm hg
<b>Boiling point/range:</b>	56 °C (132.8 °F)
<b>Melting point/ range:</b>	-95 °C (-139°F)
<b>Specific gravity:</b>	1.2
<b>Vapor density:</b>	2.0
<b>Flash point:</b>	-20 °C (-4°F)
<b>Flammable/Explosive limits - lower:</b>	2.2 %
<b>Flammable/Explosive limits - upper:</b>	13 %
<b>Autoignition temperature:</b>	465 °C (869°F)
<b>Evaporation rate:</b>	14.4
<b>Solubility in water:</b>	Soluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	778 g/l (calculated)

Viscosity: Not available.  
 Decomposition temperature: Not available.

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions of storage and use.

**Hazardous reactions:** Will not occur.

**Hazardous decomposition products:** Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

**Incompatible materials:** This product may react with oxidizing agents.

**Reactivity:** Not available.

**Conditions to avoid:** Heat, flames, sparks and other sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

**Inhalation:** Causes respiratory tract irritation. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.

**Skin contact:** Causes skin irritation. Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** May cause gastrointestinal tract irritation if swallowed. May cause dizziness, incoordination, headache, nausea, and vomiting.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Propane/Isobutane	None	No Records
Acetone	Oral LD50 (RABBIT) = 5,340 mg/kg Oral LD50 (RAT) = 5,800 mg/kg Oral LD50 (RAT) = 9,800 mg/kg Dermal LD50 (RABBIT) = 20,000 mg/kg Inhalation LC50 (RAT, 8 h) = 50.1 mg/l Inhalation LC50 (RAT, 4 h) = 76 mg/l	Blood, Central nervous system, Irritant, Reproductive
Methyl ethyl ketone	Oral LD50 (RAT) = 2,300 - 3,500 mg/kg Oral LD50 (RAT) = 4,500 - 6,800 mg/kg Dermal LD50 (RABBIT) = > 8,000 mg/kg Inhalation LC50 (RAT, 4 h) = 11700 ppm	Irritant, Central nervous system
Ethylcellulose	None	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Propane/Isobutane	No	No	No
Acetone	No	No	No
Methyl ethyl ketone	No	No	No
Ethylcellulose	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.  
**Hazardous waste number:** D001: Ignitable. D035: Methyl Ethyl Ketone. D018: Benzene.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Aerosols, flammable  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None  
**DOT Hazardous Substance(s):** Acetone, Methyl ethyl ketone

#### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Aerosols, flammable  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

#### Water Transportation (IMO/IMDG)

**Proper shipping name:** AEROSOLS  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12 (b) Export Notification:** None above reporting de minimis  
**CERCLA/SARA Section 302 EHS:** None above reporting de minimis  
**CERCLA/SARA Section 311/312:** Immediate Health, Fire, Delayed Health  
**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methyl ethyl ketone (CAS# 78-93-3).  
**CERCLA Reportable quantity:** Acetone (CAS# 67-64-1) 5,000 lbs. (2,270 kg)  
Methyl ethyl ketone (CAS# 78-93-3) 5,000 lbs. (2,270 kg)  
**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

#### Canada Regulatory Information

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

**Prepared by:** Lou Fabrizio, Regulatory Affairs Specialist

**Issue date:** 10/07/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.