



Startex Paint Thinner

**Safety Data Sheet**  
**Startex Paint Thinner**

Version 1.3

Revision Date: 05/19/2017

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product name** : Startex Paint Thinner

**Recommended use of the chemical and restrictions on use**

**Recommended use** : Thinner

**Manufacturer or supplier's details**

**Company** : Nexeo Solutions LLC - STARTEX™  
**Address** : 3 Waterway Square Place Suite 1000  
The Woodlands, TX. 77380  
United States of America

**Emergency telephone number:**

Health North America: 1-855-NEXEO4U (1-855-639-3648)

Health International: 1-855-NEXEO4U (1-855-639-3648)

Transport North America: CHEMTREC (1-800-424-9300)

**Additional Information:** : Responsible Party: Product Safety Group  
E-Mail: [msds@nexeosolutions.com](mailto:msds@nexeosolutions.com)  
SDS Requests: 1-855-429-2661  
SDS Requests Fax: 1-281-500-2370  
Website: [www.nexeosolutions.com](http://www.nexeosolutions.com)

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 1B

Carcinogenicity : Category 2

Specific target organ toxicity : Category 3 (Central nervous system)  
- single exposure

Specific target organ toxicity : Category 1 (Central nervous system)  
- repeated exposure

Aspiration hazard : Category 1

**GHS Label element**



## Safety Data Sheet Startex Paint Thinner

Version 1.3

Revision Date: 05/19/2017

Hazard pictograms



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H340 May cause genetic defects.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.



## Safety Data Sheet Startex Paint Thinner

Version 1.3

Revision Date: 05/19/2017

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

CAS-No.	Chemical Name	Weight %
64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med aliph.	70 - 90
8052-41-3	Stoddard solvent	20 - 30
1330-20-7	**Mixed Xylenes	1 - 5
95-63-6	**1,2,4-trimethylbenzene	1 - 5
111-84-2	**Nonane	1 - 5
100-41-4	**Ethylbenzene	0.1 - 1
91-20-3	**Naphthalene	0.1 - 1

Any Concentration shown as a range is due to batch variation.

**Special Notes:** : \*\* Other substances in the product which may present a health or environmental hazard.

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.



## Safety Data Sheet Startex Paint Thinner

Version 1.3

Revision Date: 05/19/2017

- Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use a water spray to cool fully closed containers.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform



**Safety Data Sheet**  
**Startex Paint Thinner**

Version 1.3

Revision Date: 05/19/2017

respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med aliph.	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0
8052-41-3	Stoddard solvent	TWA	100 ppm	ACGIH



**Safety Data Sheet  
Startex Paint Thinner**

Version 1.3

Revision Date: 05/19/2017

		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
1330-20-7	**Mixed Xylenes	TWA	100 ppm 435 mg/m3	OSHA Z-1
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
95-63-6	**1,2,4-trimethylbenzene	TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
111-84-2	**Nonane	TWA	200 ppm	ACGIH
		TWA	200 ppm 1,050 mg/m3	NIOSH REL
		TWA	200 ppm 1,050 mg/m3	OSHA P0
100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
91-20-3	**Naphthalene	TWA	10 ppm	ACGIH
		TWA	10 ppm 50 mg/m3	NIOSH REL
		ST	15 ppm 75 mg/m3	NIOSH REL
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		TWA	10 ppm 50 mg/m3	OSHA P0
		STEL	15 ppm 75 mg/m3	OSHA P0

**Personal protective equipment**

Respiratory protection

: No personal respiratory protective equipment normally required.  
In the case of vapour formation use a respirator with an approved filter.



## Safety Data Sheet Startex Paint Thinner

Version 1.3

Revision Date: 05/19/2017

### Hand protection

- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : clear, colourless
- Odour : mild, characteristic
- Odour Threshold : No data available
- pH : No data available
- Freezing Point : No data available
- Boiling Point (Boiling point/boiling range) : 158 - 198 °C (316 - 388 °F)
- Flash point : 39.44 - 45 °C (102.99 - 113 °F)  
Method: Tag closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : 0.0083 PSI @ 20 °C (68 °F)
- Relative vapour density : No data available
- Relative density : 0.775 - 0.784 @ 20 °C (68 °F)  
Reference substance: (water = 1)



## Safety Data Sheet Startex Paint Thinner

Version 1.3

Revision Date: 05/19/2017

Density	: No data available
Solubility(ies) Water solubility	: Negligible
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: 276 °C
Thermal decomposition	: No data available
VOC	: 100.0 % / 781.27 g/l / 6.52 lb/gal
Non VOC	: 0.0 % / 0.00 g/l / 0.00 lb/gal
VOC Vapor Pressure	: 0.0083 PSI
Hazardous Air Pollutants (HAPS)	: 0.0 % / 0.00 g/l / 0.00 lb/gal

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reac- tions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: Oxidizing agents Peroxides Reducing agents Strong bases
Hazardous decomposition products	: Carbon oxides

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

##### Product:

Acute dermal toxicity : Acute toxicity estimate: 2,505 mg/kg





## Safety Data Sheet Startex Paint Thinner

Version 1.3

Revision Date: 05/19/2017

### Components:

**64742-47-8 / 64742-88-7:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### Skin corrosion/irritation

#### Product:

Result: Irritating to skin.

### Components:

**64742-47-8 / 64742-88-7:**

Species: Rabbit

Exposure time: 24 h

Result: Irritating to skin.

### Serious eye damage/eye irritation

#### Product:

Result: Irritating to eyes.

### Components:

**64742-47-8 / 64742-88-7:**

Species: Rabbit

Result: Irritating to eyes.

### Respiratory or skin sensitisation

#### Components:

**64742-47-8 / 64742-88-7:**

Test Type: Buehler Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

### Germ cell mutagenicity

#### Components:

**64742-47-8 / 64742-88-7:**

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

**8052-41-3:**

Germ cell mutagenicity - Assessment : Positive result(s) from mutagenicity tests in mammals. Evidence that the substance has potential to cause mutations to germ cells



## Safety Data Sheet Startex Paint Thinner

Version 1.3

Revision Date: 05/19/2017

### Carcinogenicity

#### Components:

**64742-47-8 / 64742-88-7:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

**8052-41-3:**

Carcinogenicity - Assessment : Possible human carcinogen

#### IARC

Group 2B: Possibly carcinogenic to humans

100-41-4

\*\*Ethylbenzene

91-20-3

\*\*Naphthalene

#### OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### NTP

Reasonably anticipated to be a human carcinogen

91-20-3

\*\*Naphthalene

#### ACGIH

Confirmed animal carcinogen with unknown relevance to humans

100-41-4

\*\*Ethylbenzene

### Reproductive toxicity

#### Components:

**64742-47-8 / 64742-88-7:**

Reproductive toxicity - Assessment : Animal testing did not show any effects on fertility.

Teratogenicity - Assessment : Embryotoxicity classification not possible from current data.

**8052-41-3:**

Reproductive toxicity - Assessment : Fertility classification not possible from current data.

Teratogenicity - Assessment : Embryotoxicity classification not possible from current data.

### STOT - single exposure

#### Components:

**64742-47-8 / 64742-88-7:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as



## Safety Data Sheet Startex Paint Thinner

Version 1.3

Revision Date: 05/19/2017

specific target organ toxicant, single exposure, category 3 with narcotic effects.

### STOT - repeated exposure

#### Components:

##### 8052-41-3:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

### Aspiration toxicity

#### Product:

May be fatal if swallowed and enters airways.

#### Components:

##### 64742-47-8 / 64742-88-7:

May be fatal if swallowed and enters airways.

### Further information

#### Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### 64742-47-8 / 64742-88-7:

- |   |   |
|---|---|
| Toxicity to fish                                    | : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l<br>Exposure time: 96 h<br>Test Type: semi-static test                                |
| Toxicity to daphnia and other aquatic invertebrates | : EL50 (Daphnia magna (Water flea)): 1.4 mg/l<br>Exposure time: 48 h<br>Test Type: static test  |
| Toxicity to algae                                   | : EL50 (Pseudokirchneriella subcapitata (green algae)): 1 mg/l<br>End point: Growth rate<br>Exposure time: 72 h<br>Test Type: static test |
| Acute aquatic toxicity- Assessment                  | : Toxic to aquatic life.  |
| Chronic aquatic toxicity- Assessment                | : Toxic to aquatic life with long lasting effects.  |



## Safety Data Sheet Startex Paint Thinner

Version 1.3

Revision Date: 05/19/2017

essment

### Persistence and degradability

#### Components:

**64742-47-8 / 64742-88-7:**

Biodegradability : aerobic  
Biodegradation: 61 %  
Exposure time: 28 d  
Remarks: Readily biodegradable

### Bioaccumulative potential

#### Components:

**1330-20-7:**

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

**95-63-6:**

Partition coefficient: n-octanol/water : Remarks: No data available

**91-20-3:**

Partition coefficient: n-octanol/water : log Pow: 3.4 (25 °C)  
pH: 7 - 7.5

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.  
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact



**Safety Data Sheet  
Startex Paint Thinner**

Version 1.3

Revision Date: 05/19/2017

NEXEO's Environmental Services Group at 800-637-7922.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

**DOT (Department of Transportation):**  
UN1263, PAINT RELATED MATERIAL, 3, III

**IATA (International Air Transport Association):**  
UN1263, PAINT RELATED MATERIAL, 3, III

**IMDG (International Maritime Dangerous Goods):**  
UN1263, PAINT RELATED MATERIAL, 3, III, Marine Pollutant (MIXTURE OF PETROLEUM DISTILLATES)  
(PETROLEUM DISTILLATE, HYDROTREATED LIGHT, STODDARD SOLVENT) , Flash Point:39.44 - 45  
°C(102.99 - 113 °F)

**Special Notes:** : The flash point for this material is greater than 100 F (38 C).  
Therefore, in accordance with 49 CFR 173.150(f) non-bulk  
containers (<450L or <119 gallon capacity) of this material  
may be shipped as non-regulated when transported solely by  
land, as long as the material is not a hazardous waste, a  
marine pollutant, or specifically listed as a hazardous substance.

**SECTION 15. REGULATORY INFORMATION**

**WHMIS Classification** : B3: Combustible Liquid  
D2A: Very Toxic Material Causing Other Toxic Effects  
D2B: Toxic Material Causing Other Toxic Effects

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
**Mixed Xylenes	1330-20-7	100	2505

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Chronic (Delayed) Health Hazard  
Immediate (Acute) Health Hazard

**SARA 302** : No chemicals in this material are subject to the reporting re-  
quirements of SARA Title III, Section 302.



# Safety Data Sheet Startex Paint Thinner

Version 1.3

Revision Date: 05/19/2017

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

1330-20-7	**Mixed Xylenes
95-63-6	**1,2,4-trimethylbenzene
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene

## Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

1330-20-7	**Mixed Xylenes
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene
98-82-8	**Cumene
108-88-3	**Toluene
71-43-2	**Benzene

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

1330-20-7	**Mixed Xylenes
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene
98-82-8	**Cumene
108-88-3	**Toluene
71-43-2	**Benzene

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

1330-20-7	**Mixed Xylenes
100-41-4	**Ethylbenzene
98-82-8	**Cumene
108-88-3	**Toluene
71-43-2	**Benzene

## Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

1330-20-7	**Mixed Xylenes
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene
108-88-3	**Toluene
71-43-2	**Benzene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

1330-20-7	**Mixed Xylenes
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene
108-88-3	**Toluene
71-43-2	**Benzene

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

## US State Regulations

### Massachusetts Right To Know

8052-41-3	Stoddard solvent	20 - 30 %
1330-20-7	**Mixed Xylenes	1 - 5 %
95-63-6	**1,2,4-trimethylbenzene	1 - 5 %



## Safety Data Sheet Startex Paint Thinner

Version 1.3

Revision Date: 05/19/2017

111-84-2	**Nonane	1 - 5 %
71-43-2	**Benzene	0 - 0.1 %
<b>Pennsylvania Right To Know</b>		
64742-47-8 /	Distillates (pet), hydrotreated light AND/OR	70 - 90 %
64742-88-7	Solvent naphtha (pet), med aliph.	
8052-41-3	Stoddard solvent	20 - 30 %
1330-20-7	**Mixed Xylenes	1 - 5 %
95-63-6	**1,2,4-trimethylbenzene	1 - 5 %
111-84-2	**Nonane	1 - 5 %
100-41-4	**Ethylbenzene	0.1 - 1 %
91-20-3	**Naphthalene	0.1 - 1 %
98-82-8	**Cumene	0 - 0.1 %
108-88-3	**Toluene	0 - 0.1 %
71-43-2	**Benzene	0 - 0.1 %
<b>New Jersey Right To Know</b>		
64742-47-8 /	Distillates (pet), hydrotreated light AND/OR	70 - 90 %
64742-88-7	Solvent naphtha (pet), med aliph.	
8052-41-3	Stoddard solvent	20 - 30 %
1330-20-7	**Mixed Xylenes	1 - 5 %
95-63-6	**1,2,4-trimethylbenzene	1 - 5 %
111-84-2	**Nonane	1 - 5 %
100-41-4	**Ethylbenzene	0.1 - 1 %
91-20-3	**Naphthalene	0.1 - 1 %
<b>California Prop 65</b>		
	WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
108-88-3	**Toluene	
71-43-2	**Benzene	
	WARNING! This product contains a chemical known to the State of California to cause cancer.	
100-41-4	**Ethylbenzene	
91-20-3	**Naphthalene	
98-82-8	**Cumene	
71-43-2	**Benzene	

### The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory




**Safety Data Sheet  
Startex Paint Thinner**

Version 1.3

Revision Date: 05/19/2017

**SECTION 16. OTHER INFORMATION**

**NFPA:**



**HMIS III:**

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>2</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

**Revision Date** : 05/19/2017

**Material number:**

16067564, 16067563, 16067562, 16067561, 16067560, 16067559, 16067558, 16067557,  
16056402, 16056401, 16056400, 16056399, 16056398, 16056397, 16056396, 16056395,  
16056394

<b>Key or legend to abbreviations and acronyms used in the safety data sheet</b>			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances





**Safety Data Sheet**  
**Startex Paint Thinner**

Version 1.3

Revision Date: 05/19/2017

MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50			Lethal Concentration 50%